

Item No		Quantity	Rate	Amount
	<u>BILL NO. 1</u>			
	<u>PRELIMINARIES</u>			
	<u>SUPPLEMENTARY PREAMBLES</u>			
	<u>Meaning of terms "Tender" and "Tenderer"</u>			
	Any reference to the words "Tender" or "Tenderer" herein and/or in any other documentation shall be construed to have the same meaning as the words "Bid" or "Bidder"			
	<u>Preliminaries</u>			
	<u>NOTES</u>			
	1. Second edition of June 2005) in conjunction with the Contract Data is taken to be incorporated herein.			
	2. The Tenderer is deemed to have taken cognizance of the above mentioned documents for the full intent and meaning of each clause. These clauses are referred to by clause number and heading only.			
	3. Where standard clauses or options are not applicable to this contract such modifications, corrections or supplements as are necessary, are given under each relevant clause.			
	4. Where any items are not used for this specific contract such items are nevertheless listed but marked not applicable in the amount column.			
	5. The amount of the Preliminaries to be included in each monthly payment certificate shall be assessed as an amount prorated to the value of the work duly executed in the same ratio as the preliminaries bears to the total of prices excluding any contingency sum, the amount for the Preliminaries and any amount in respect of contract price adjustment provided for in the contract.			
	Carried to Summary			
	Section No. 1			
	PRELIMINARIES			
	Bill No. 1			
	PRELIMINARIES AND GENERAL			
	JMQS			
			R	

6. Where the initial contract period is extended, the monthly charge shall be calculated on the basis as set out in (v) but taking into account the revised period for completing the works.
7. The amount or the items of the Preliminaries are adjusted to take account of the theoretical financial effect which changes in time or value (or both) have on this section. Such adjustments are based on adjustments in the following categories as recorded in the Bill of Quantities:
 - an amount which is not varied, namely Fixed
 - an amount which is varied in proportion to the contract value, namely Value Related; and
 - an amount which is varied in proportion to the construction period as compared to the initial construction period excluding revisions to the construction period for which the contractor is not entitled to adjustment in terms of the contract, namely Time Related.
8. Where no provision is made in the Bill of Quantities to indicate which of the three categories in (vii) apply or where no selection is made, the adjustments shall be based on the following breakdown:
 - 10 percent is Fixed;
 - 55 percent is Value Related
 - 35 percent is Time Related
9. The adjustment of the Preliminaries shall apply notwithstanding the actual employment of resources in the execution of the works. The contract value used for the adjustment of the Preliminaries shall exclude any contingency sum, the amount for the Preliminaries and any amount in respect of contract price adjustment provided for in the contract. Adjustments in respect of any staged or sectional completion shall be prorated to the value of each section.
10. Items not priced in these preliminaries are deemed to be included elsewhere in this bill of quantities.

Carried to Summary

Section No. 1
PRELIMINARIES
Bill No. 1
PRELIMINARIES AND GENERAL
JMQS

R

SECTION A: CORE CLAUSES

GENERAL (A1)

- 1 Clause 1.0
Clause 11.2(4) is amended by replacing it with the following:
The Contract Date is the date when the contractor receives one fully completed signed copy of this document, including the schedule of deviations (if any) as contained in the Form of Offer and Acceptance

Fixed:.....

Value Related:.....

Time Related:.....

Item

THE CONTRACTOR'S MAIN RESPONSIBILITIES (A2)

- 2 Clause 2.0
The contractor must provide and keep a copy of the NEC3 Engineering and Construction Contract - Option B: Priced contract with bill of quantities applicable to this contract and a copy of the Procurement Document on the site, to which the Project Manager and Supervisor have access at all times

Fixed:.....

Value Related:.....

Time Related:.....

Item

TIME (A3)

- 3 Clause 3.0

Fixed:.....

Value Related:.....

Time Related:.....

Item

Carried to Summary

R

Section No. 1
PRELIMINARIES
Bill No. 1
PRELIMINARIES AND GENERAL
JMQS

	<u>TESTING AND DEFECTS (A4)</u>			
4	Clause 4.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>PAYMENT (A5)</u>			
5	Clause 5.0 Clause 50.0 is amended by the addition of the following clause: Materials and goods stored off site are not included in the amount authorised for payment Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>COMPENSATION EVENTS (A6)</u>			
6	Clause 6.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>TITLE (A7)</u>			
7	Clause 7.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	Carried to Summary		R	
	Section No. 1 PRELIMINARIES Bill No. 1 PRELIMINARIES AND GENERAL JMQS			

	<u>RISKS AND INSURANCE (A8)</u>			
8	Clause 8.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>TERMINATION (A9)</u>			
9	Clause 9.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>SECTION B: MAIN OPTION CLAUSES</u>			
	<u>PRICED CONTRACT WITH BILL OF QUANTITIES (B1)</u>			
	<u>Clause 10.0</u> <u>The quantities in provisional bills of quantities are a n indication of the works tobe executed and are subj ect to remeasurement</u>			
10	Clause 10.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>SECTION C: DISPUTE RESOLUTION</u>			

[illegible]

	<u>X4 PARENT COMPANY GUARANTEE (D4)</u>			
15	Clause 15.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>X5 SECTIONAL COMPLETION (D5)</u>			
16	Clause 16.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>X6 BONUS FOR EARLY COMPLETION (D6)</u>			
17	Clause 17.0 Fixed:..... Value Related:..... Time Related:.....	Item		
	<u>X7 DELAY DAMAGES (D7)</u>			
18	Clause 18.0 Fixed:..... Value Related:..... Time Related:.....	Item		
Carried to Summary			R	
Section No. 1 PRELIMINARIES Bill No. 1 PRELIMINARIES AND GENERAL JMQS				

[illegible]

[illegible]

<u>Z ADDITIONAL CONDITIONS OF CONTRACT (D16)</u>				
27	Clause 27.0 Fixed:..... Value Related:..... Time Related:.....	Item		
<u>SECTION E: CONTRACT DATA</u>				
<u>CONTRACT DATA (E1)</u>				
28	Clause 28 Tenderers are referred to Part C1.2 Contract Data for variables pertaining to this contract Fixed:..... Value Related:..... Time Related:.....	Item		
<u>SECTION F: SPECIFIC PRELIMINARIES</u>				
<u>PART C3.1 SCOPE OF WORKS PLANT AND MATERIALS (4.2)</u>				
29	Materials, Samples and Shop drawings (4.2.2) Fixed:..... Value Related:..... Time Related:.....	Item		
30	Instruction Manuals and Guarantees (4.2.3) Fixed:..... Value Related:..... Time Related:.....	Item		
Carried to Summary			R	
Section No. 1 PRELIMINARIES Bill No. 1 PRELIMINARIES AND GENERAL JM QS				

31	<p>Training staff of the Employer (4.2.4)</p> <p>Fixed:.....</p> <p>Value Related:.....</p> <p>Time Related:.....</p> <p><u>SITE ESTABLISHMENT (4.5)</u></p>	Item		
32	<p>Facilities provided by the contractor - site office and storage stores (4.5.2)</p> <p>Fixed:.....</p> <p>Value Related:.....</p> <p>Time Related:.....</p>	Item		
33	<p>Other Facilities and Services - Water, Electricity, Ablution and Telecommunication services/facilities (4.5.4)</p> <p>Fixed:.....</p> <p>Value Related:.....</p> <p>Time Related:.....</p>	Item		
34	<p>Notice Boards (4.5.7)</p> <p>Fixed:.....</p> <p>Value Related:.....</p> <p>Time Related:.....</p>	Item		
35	<p>Survey control and Setting out of the works (4.10)</p> <p>Fixed:.....</p> <p>Value Related:.....</p> <p>Time Related:.....</p>	Item		
Carried to Summary			R	
<p>Section No. 1 PRELIMINARIES Bill No. 1 PRELIMINARIES AND GENERAL JMQS</p>				

<u>MANAGEMENT OF THE WORKS (5.1)</u>				
36	Planning and programming (5.1.3) Fixed:..... Value Related:..... Time Related:.....	Item		
37	Software application for programming (5.1.4) Fixed:..... Value Related:..... Time Related:.....	Item		
38	Testing, completion, commissioning and correction of defects (5.1.11) Fixed:..... Value Related:..... Time Related:.....	Item		
39	Recording of weather (5.1.12) Fixed:..... Value Related:..... Time Related:.....	Item		
40	Management meetings (5.1.15) Fixed:..... Value Related:..... Time Related:.....	Item		
Carried to Summary			R	
Section No. 1 PRELIMINARIES Bill No. 1 PRELIMINARIES AND GENERAL JMQS				

[illegible]

46	Compliance with HIV/Aids awareness (5.2.6)				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
47	Compliance with OHS ACT and Construction Regulation 2014				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
48	Health ans safety file				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
49	OHS training				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
50	Enclosure of Works				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
Carried to Summary				R	
Section No. 1					
PRELIMINARIES					
Bill No. 1					
PRELIMINARIES AND GENERAL					
JMQS					

51	Resting/Eating area Fixed:..... Value Related:..... Time Related:.....	Item
52	Ablution and latrine facilities Fixed:..... Value Related:..... Time Related:.....	Item
53	Security Fixed:..... Value Related:..... Time Related:.....	Item
54	COVID-19 compliance Fixed:..... Value Related:..... Time Related:.....	Item
55	Water Fixed:..... Value Related:..... Time Related:.....	Item
Carried to Summary		R
Section No. 1 PRELIMINARIES Bill No. 1 PRELIMINARIES AND GENERAL JMQS		

56	First aid kit	
	Fixed:.....	
	Value Related:.....	
	Time Related:.....	Item
57	Provision of PPE	
	Fixed:.....	
	Value Related:.....	
	Time Related:.....	Item
58	Medical certificates of fitness	
	Fixed:.....	
	Value Related:.....	
	Time Related:.....	Item
<u>ENVIRONMENTAL MANAGEMENT PROGRAMME</u>		
<u>It is required of the contractor to thoroughly study the Environmental Management Programme Specification (attached herewith under part C3 - Scope of Works) that must be read together with and is deemed to be incorporated under this Section of the bills of quantities</u>		
59	Compliance to Environmental Management Programme (EMPR)/ Environmental Authorisation (EA) and Water Use License (WUL) (5.3.1)	
	Fixed:.....	
	Value Related:.....	
	Time Related:.....	Item

Carried to Summary

R

**Section No. 1
PRELIMINARIES
Bill No. 1
PRELIMINARIES AND GENERAL
JMQS**

60	Rehabilitation Measures (including hydro seeding/ revegetation) (5.3.2)				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
61	Waste management and disposal (including obtaining safe disposal slips from disposal facilities/ service providers); (5.3.3)				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
62	Provision of chemical toilets (if no municipal connection) (5.3.4)				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
63	Removal of excess spoil from site (if any). (5.3.5)				
	Fixed:.....				
	Value Related:.....				
	Time Related:.....	Item			
				R	
Carried to Summary					
Section No. 1					
PRELIMINARIES					
Bill No. 1					
PRELIMINARIES AND GENERAL					
JMQS					

<p>Section No. 1</p> <p>Bill No. 1</p> <p>PRELIMINARIES AND GENERAL</p> <p><u>SUMMARY</u></p>			
<p>Total Brought Forward from Page No.</p>	<p>Page No</p>		<p>Amount</p>
	1		
	2		
	3		
	4		
	5		
	6		
	7		
	8		
	9		
	10		
	11		
	12		
	13		
	14		
	15		
	16		
	17		
<p>Total Carried to Final Summary</p> <p>Section No. 1</p> <p>PRELIMINARIES</p> <p>Bill No. 1</p> <p>PRELIMINARIES AND GENERAL</p> <p>JMQS</p>		<p>R</p>	

Item No	Quantity	Rate	Amount
<u>BILL No. 1</u>			
<u>FOUNDATIONS (PROVISIONAL)</u>			
<u>PREAMBLES</u>			
For preambles see " Specification of materials and methods to be used - PW 371" as published by the National Department of Public Works			
Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to.			
Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.			
<u>SUPPLEMENTARY PREAMBLES</u>			
<u>Nature of ground</u>			
The nature of the ground is assumed to be loose sandy material, therefore "earth", but possibly interspersed with "hard rock" and/or "soft rock".			
<u>Excavation for working space in rock</u>			
Notwithstanding clause 11 page 8 of the Standard System of Measuring Building Work, excavation for working space in rock will be measured in cubic metres to the extent executed and given as "extra over" bulk excavation or trench and hole excavation as the case may be			
<u>Carting away of excavated material</u>			
Descriptions of carting away of excavated material shall be deemed to include loading excavated material onto trucks directly from the excavations or, alternatively, from stock piles situated on the building site			
Carried to Summary			
			R
Section No. 2			
BUILDING WORKS			
Bill No. 1			
FOUNDATIONS (PROVISIONAL)			
JMQS			

<u>Filling</u>					
Notwithstanding the reference to prescribed multiple handling in clause 1 page 6 of the Standard System of Measuring Building Work, prices for filling and backfilling shall include for all selection and any multiple handling of material					
<u>EXCAVATION</u>					
<u>Excavate in earth not exceeding 2m deep below natural, elevated or reduced ground level for</u>					
1	Trenches	m3	239		
2	Staircase bases	m3	8		
<u>SUNDRIES</u>					
<u>Extra over trench and hole excavations in earth for excavation in</u>					
3	Extra over excavations in earth for trenches and holes for excavations in soft rock	m3	124		
4	Extra over excavations in earth for trenches and holes for excavations in hard rock	m3	124		
<u>Extra over all excavations for carting away</u>					
5	Extra over all excavations for carting away surplus material from excavations and/or from stockpiles on site to a dumping site to be located by the Contractor	m3	139		
<u>Risk of collapse of excavations</u>					
6	Risk of collapse of sides of excavations for trenches and holes from natural, elevated or reduced ground level to not exceeding 1,5m deep	m2	589		
<u>Keeping excavations free of water</u>					
7	Allow for keeping excavations free of all water other than subterranean water		Item		
Carried to Summary				R	
Section No. 2 BUILDING WORKS Bill No. 1 FOUNDATIONS (PROVISIONAL) JMQS					

<u>FILLING, etc.</u>				
8	Backfilling from the excavations to trenches and holes compacted to 90% modified AASHTO density	m3		
9	Earth filling from the excavations to under floors, steps, pavings, etc compacted to 90% modified AASHTO density	m3		
10	Imported earth filling supplied by the Contractor and brought onto site, under floors, steps, pavings, etc. compacted to 90% modified AASHTO density	m3	269	
11	50mm thick dry, clean, washed riversand layer evenly spread over filling (elsewhere measured), levelled, watered and rammed to receive waterproof membrane (elsewhere measured) under solid floors	m2	537	
<u>Compaction of surfaces</u>				
12	Compaction of ground surface under trenches, holes etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 93% Mod AASHTO density	m2	280	
13	Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 93% Mod AASHTO density	m2	537	
<u>Prescribed density tests on filling</u>				
14	Tests to determine the degree of compaction, etc. of ground or filling	No	16	
<u>PROTECTION AGAINST TERMITES</u>				
15	To bottoms and sides of trenches, bases, etc	m2	869	
16	Poisoning surface of ground or filling under floors, steps, etc. including raking out 75mm deep V-shaped channels against the walls, etc. treating with poison solution, backfilling and ramming	m2	537	
Carried to Summary				
Section No. 2 BUILDING WORKS Bill No. 1 FOUNDATIONS (PROVISIONAL) JMQS			R	

<u>UNREINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES</u>					
<u>15MPa/20mm concrete blinding</u>					
17	Blinding	m3	14		
<u>REINFORCED CONCRETE CAST AGAINST EXCAVATED SURFACES</u>					
<u>30MPa/20mm concrete</u>					
18	In footings to walls cast against excavated surfaces, stepped and levelled	m3	87		
<u>TEST CUBES</u>					
19	Prepare set of three 150 x 150 x 150mm concrete strength test cubes, label and send to an approved laboratory for testing, pay all charges and submit report to the Representative/Agent. Only successful tests will be paid for (<u>Provisional</u>)	No	7		
<u>REINFORCEMENT</u>					
<u>Steel bar reinforcement to structural concrete work</u>					
20	Various diameter steel reinforcing bars	t	13.92		
<u>MASONRY</u>					
<u>Brickwork of NFX bricks (14 MPa nominal compressive strength) in class 1 mortar</u>					
21	One brick wall	m2	369		
22	Two brick wall	m2	3		
<u>Brick reinforcement</u>					
23	Brick reinforcement 150mm wide built into brick walls with sufficient laps at end joints, angles and intersections (measured net)	m	4 339		
<u>FACE BRICKWORK</u>					
Carried to Summary				R	
Section No. 2 BUILDING WORKS Bill No. 1 FOUNDATIONS (PROVISIONAL) JMQS					

[illegible]

<p>Section No. 2</p> <p>Bill No. 1</p> <p>FOUNDATIONS (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	19			
	20			
	21			
	22			
	23			

Carried Forward to Summary of Section No. 2

R

Section No. 2
BUILDING WORKS
Bill No. 1
FOUNDATIONS (PROVISIONAL)
JMQS

Formwork

Descriptions of formwork shall be deemed to include use and waste only (except where described as "left in" or "permanent"), for fitting together in the required forms, wedging, plumbing and fixing to true angles and surfaces as necessary to ensure easy release during stripping and for reconditioning as necessary before re-use. The vertical strutting shall be carried down to such construction as is sufficiently strong to afford the required support without damage and shall remain in position until the newly constructed work is able to support itself.

Formwork to soffits of (solid) slabs etc shall be deemed to be to slabs not exceeding 250mm thick unless otherwise described

Formwork to sides of bases, pile caps, ground beams, etc, will only be measured where it is prescribed by the engineer for design reasons. Formwork necessitated by irregularity or collapse of excavated faces will not be measured and the cost thereof shall be deemed to be included in the allowance for taking the risk of collapse of the sides of the excavations, provision for which is made in "Foundations"

CONCRETE

REINFORCED CONCRETE

25MPa/20mm concrete

1	Blinding	m3	40	
---	----------	----	----	--

30MPa/19mm concrete

2	Thickened slab on waterproofing	m3	3	
3	Surface beds on waterproofing	m3	48	
4	Slabs, including beams and inverted beams	m3	142	
5	Stairs and landing	m3	9	

TEST CUBES

Carried to Summary

R

Section No. 2
BUILDING WORKS
Bill No. 2
**CONCRETEWORK, FORMWORK & REINFORCEMENTS (PR
JM QS**

<u>Concrete test cubes</u>					
6	Prepare set of three 150 x 150 x 150mm concrete strength test cubes, label and send to an approved laboratory for testing, pay all charges and submit report to the Representative/Agent. Only successful tests will be paid for <u>(Provisional)</u>	No	20		
<u>CONCRETE SUNDRIES</u>					
<u>Finishing top surfaces of concrete smooth with a wood float</u>					
7	Surface beds, slabs, etc	m2	1 090		
<u>FORMWORK</u>					
<u>Rough formwork to soffits and sides</u>					
8	Soffits of slabs, beams and stairs propped up exceeding 1.5m high and not exceeding 3.5m high	m2	585		
9	Soffits of slabs and beams propped up not exceeding 6.0m high and not exceeding 7.5m high	m2	10		
10	Sides of slabs and beams propped up	m2	124		
11	Edges, risers, ends and reveals not exceeding 300mm high or wide	m	345		
<u>MOVEMENT JOINTS ETC</u>					
12	10mm saw cut joints	m	50		
13	10mm construction joints	m	63		
<u>REINFORCEMENT</u>					
<u>Steel bar reinforcement to structural concrete work</u>					
14	Various diameter steel reinforcing bars	t	15.25		
Carried to Summary				R	
Section No. 2					
BUILDING WORKS					
Bill No. 2					
CONCRETEWORK, FORMWORK & REINFORCEMENTS (PR					
JMQS					

MESH REINFORCEMENT

[illegible]

Section No. 2				
Bill No. 2				
CONCRETEWORK, FORMWORK & REINFORCEMENTS (PROVISIONAL)				
<u>SUMMARY</u>				
	Page No		Amount	
Total Brought Forward from Page No.	25			
	26			
	27			
	28			
Carried Forward to Summary of Section No. 2			R	
Section No. 2				
BUILDING WORKS				
Bill No. 2				
CONCRETEWORK, FORMWORK & REINFORCEMENTS (PR				
JMQS				

Face bricks

Bricks shall be ordered timeously to obtain uniformity in size and colour

Pointing

Descriptions of recessed pointing to fair face brickwork and face brickwork shall be deemed to include square recessed, hollow recessed, weathered pointing, etc

SAMPLES

Samples of all masonry building units, shall consist of a minimum of 6 units

STONEMWORK

Slate, marble, granite, etc

Slate, marble, granite, etc is to be best quality stone from an approved quarry, free from cracks and other defects and equal to samples to be submitted to and approved by the architect. Each stone is to hold its full size, square to the back and to be set on its natural quarry bed

Setting out

Care shall be exercised in setting out the work, the preparation of templates and the checking of the detail drawings. All measurements shall be taken on the site where necessary and the full size setting out of each course shall be done at the yard so as to ensure the proper fitting of each stone

Before putting any work in hand the contractor is to submit to the architect for his approval details of the manner in which he proposes to set out the slabs and joints in all wall facings, pavings, sills, treads, etc together with samples of grain or pattern matching

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 3
MASONRY (PROVISIONAL)
JMQS

R

Face labours

Face labours are to match samples to be submitted to and approved by the architect Arrises are to be clean and sharp except to treads and thresholds where they are to be slightly rounded

Bedding and jointing

Slate, marble, granite and other floor paving and wall linings are to be bedded solidly on the mortar thicknesses described and are to have tightly fitting butt joints unless otherwise stated Where stonework is to be fixed with adhesive, the adhesive is to be "TAL Goldstar/Bond" (mixed 20kg/5 litre) for external use or where white or light coloured marble is used, "TAL Goldstar" for internal use or other approved. The contractor will be liable for any defects to the slate, marble and granite arising from the use of the adhesive

Where soffit linings are suspended the suspension system must be concealed and must be submitted to the architect for approval before work commences Where tolerance screws are required these are to be stainless steel expanding bolt type with matching stainless steel bracket and PVC clad dowel with nuts and washers etc

Damaged work

Any damaged stonework shall be discarded and replaced at the contractor's expense. No touching up will be permitted except in exceptional cases, with the architect's consent

Descriptions

Descriptions of stonework shall be deemed to include preparatory work, labours to backs, beds and joints, templates, mortices for bolts etc and for hoisting and setting in position, bedding, jointing and pointing, casing and protecting from injury and cleaning down at completion Descriptions of recessed pointing to stonework shall be deemed to be square recessed, hollow recessed, weathered pointing, etc

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 3
MASONRY (PROVISIONAL)
JMQS

R

TESTING OF MORTAR, ETC

1	Allow for the testing of cement sample by an approved laboratory (<u>Provisional</u>)	Item
2	Allow for the testing of 25kg fine aggregate (sand) sample by an approved laboratory (<u>Provisional</u>)	Item
3	Allow for the testing of mortar test cubes by an approved laboratory (<u>Provisional</u>)	Item

BRICKWORK

Brickwork of NFX bricks (14 MPa nominal compressive strength) in class 1 mortar

4	Piers	m3	1
5	Half brick wall	m2	309
6	Half brick linings to outer skin of one brick wall forming, edge to 255mm concrete slab	m2	41
7	Half brick wall in beamfilling	m2	38
8	One brick wall	m2	2 018
9	One and half brick wall	m2	6
10	One brick wall in beam filling	m2	437

BRICKWORK SUNDRIES

Joint forming material in movement joints

11	10mm jointex built in vertically between brick skins	m2	141
----	--	----	-----

Slip joints between horizontal brick surfaces including two layers of three-ply malthoid on bearing surfaces

12	Slip joint not exceeding 300mm wide	m2	18
----	-------------------------------------	----	----

Carried to Summary

R

Section No. 2
BUILDING WORKS
Bill No. 3
MASONRY (PROVISIONAL)
JM QS

<u>Prestressed fabricated lintels</u>					
13	100 x 70mm Lintels in lengths not exceeding 3m	m	345		
14	100 x 70mm Lintels in lengths exceeding 3m long and not exceeding 4.5m	m	92		
15	100 x 70mm Lintels in lengths exceeding 4.5m and not exceeding 6m	m	84		
<u>Brickwork reinforcement</u>					
16	13mm Chicken wire mesh in patches, fixed to brickwork	m2	624		
17	Brick reinforcement 75mm wide built into brick walls with sufficient laps at end joints, angles and intersections (measured net)	m	2 758		
18	Brick reinforcement 150mm wide built into brick walls with sufficient laps at end joints, angles and intersections (measured net)	m	16 998		
<u>Galvanised hoop iron cramps, ties, etc</u>					
19	30 x 1,6mm Wall tie 500mm long with both ends built into brickwork	No	589		
<u>SUNDRIES</u>					
20	230mm Wide turning piece to lintels etc	m	521		
<u>FACE BRICKWORK</u>					
<u>External facings in approved Country Classic Satin face bricks (FBS) pointed with square recessed horizontal and vertical joints</u>					
21	Extra over brickwork for face brickwork	m2	1 128		
22	Extra over brickwork for brick-on-edge header course lintels pointed on both faces and 220mm soffit	m	521		
23	Extra over brickwork for brick-on-edge header course cill slightly sloping	m	255		
Carried to Summary				R	
Section No. 2 BUILDING WORKS Bill No. 3 MASONRY (PROVISIONAL) JMQS					

[illegible]

<p>Section No. 2</p> <p>Bill No. 3</p> <p>MASONRY (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	30			
	31			
	32			
	33			
	34			
	35			
<p style="text-align: right;">Carried Forward to Summary of Section No. 2</p>			R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 3</p> <p>MASONRY (PROVISIONAL)</p> <p>JMQS</p>				

<u>Waterproofing to Shower Floors and Walls</u>					
<u>"Thoroseal® FX100 elastomeric" waterproofing or equal approved undre coat and two final coats all in accordance with manufacturer's recommendations</u>					
3	On concrete shower floors	m2	11		
<u>"Tal Superflex" waterproofing slurry or or equal approved</u>					
4	On shower walls	m2	40		
<u>WATERPROOFING TO ROOFS, BASEMENTS, ETC</u>					
<u>One layer Derbigum SP4 waterproofing membrane, with and including 75mm side laps and 100mm end laps, sealed to primed surface to falls and crossfalls by 'torchfusion'. (Waterproofing to be installed by an Approved Derbigum Contractor under a ten year guarantee)</u>					
5	On flat floors not exceeding 25 degrees from the horizontal, with and including 75mm side laps and 100mm end laps	m2	121		
<u>PROTECTIVE ROOFING PAINT</u>					
<u>Two coats Roofcote bituminous aluminum paint</u>					
6	On waterproofing to roofs	m2	121		
<u>JOINT SEALANTS ETC</u>					
<u>Coloured silicone sealing compound including backing cord, bond breaker, primer, etc</u>					
7	In isolation joints in floors including raking out expansion joint filler as necessary	m	536		
8	In vertical expansion joints between brickworks including raking out expansion joint filler as necessary	m	13		
9	In construction joints in floors	m	63		
10	In sawcut joints in floors	m	50		
Carried to Summary				R	
Section No. 2					
BUILDING WORKS					
Bill No. 4					
WATERPROOFING (PROVISIONAL)					
JMQS					

[illegible]

<p>Section No. 2</p> <p>Bill No. 4</p> <p>WATERPROOFING (PROVISIONAL)</p> <p><u>SUMMARY</u></p>			
Total Brought Forward from Page No.	Page No		Amount
	37		
	38		
	39		
<p style="text-align: right;">Carried Forward to Summary of Section No. 2</p>		R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 4</p> <p>WATERPROOFING (PROVISIONAL)</p> <p>JMQS</p>			

<p><u>Global Roofing Solutions 0.58mm thick 406mm cover</u> <u>Brownbuilt profile Chromadek® Z200 spelter ISQ550 Charcoal Grey finish topcoat and Pebble Grey backing coat roof sheeting, fixed to timber intermediate purlins at MAX 1200mm centres and eaves and ridge purlins at MAX 1200mm centres (final spacing to be calculated by an Engineer) using Duplex clips fixed with 10No.11 x 45mm long self-drilling wafer head PH2 screws, type 17 drill point fasteners (fastener lengths may vary depending on the insulation used or requirements), all following the manufacturer's specifications by a GRS approved contractor.</u> <u>• Brand: ArcelorMittal</u> <u>• Type of Building: Residential</u> <u>• Roof Pitch: 5.00°</u> <u>• Climatic Condition: Inland - Zone C1/C2 Low Corrosion Risk</u> <u>• Roof Profile: Brownbuilt</u> <u>• Material: Z200 spelter ISQ550 Chromadek®</u> <u>• Material Gauge: 0.58mm</u> <u>• Colour: Charcoal Grey.</u></p>						
1	Roof coverings with pitches not exceeding 25 degrees	m2	684			
2	To eaves closure	m2	82			
3	Extra over roof sheeting for bull nose bend on the eaves of the roof	m	64			
4	GSI and counter flashings to Architect's drawings	m	221			
<p><u>Lamdaboard high density closed cell Polyisocyanurate insulation colour white with Kraft facing, fixed concurrent with roof covering over purlins with "H" bar joiners screw fixed at 1200mm centres with 5mm gap between boards butt-joined over purlins</u></p>						
5	80mm Insulation closely fitted and laid roofcovering, etc	m2	684			
Carried to Summary					R	
<p>Section No. 2 BUILDING WORKS Bill No. 5 ROOF COVERING (PROVISIONAL) JM QS</p>						

<p>Section No. 2</p> <p>Bill No. 5</p> <p>ROOF COVERING (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	41			
	42			
<p style="text-align: right;">Carried Forward to Summary of Section No. 2</p>			R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 5</p> <p>ROOF COVERING (PROVISIONAL)</p> <p>JMQS</p>				

Plate nailed timber trusses shall be of approved design and manufacture and constructed with softwood structural timber by manufacture and constructed with softwood structural timber by a truss Fabricator holding a current Certificate of Competence awarded by the Institute of Timber Construction

Each roof trusses shall have all its members accurately cut and closely butted together and rigidly fixed by CSIR approved patented galvanized metal spiked pressed on both sides of each intersection by an approved connectors, precision method, all in accordance with the manufacturer's instructions

The design, manufacture and transportation of the roof trusses, bracing, etc. shall be under the control of a registered Structural Engineer in accordance with SABS 0160 and SABS 0163, who shall, after erection, provide a certificate confirming that the design, manufacture, transportation, erection and bracing has been carried out in accordance with this specification

The design shall include for all live loads, wind loads and dead loads imposed by roof covering, purlins, ceilings, etc

Fully detailed shop drawings of all trusses, etc., indicating sizes, bracing, loading, etc., shall be submitted to the Representative/Agent for approval prior to fabrication

Erection shall be carried out in accordance with the procedures and recommendations of the manual "The Erection and Bracing of Timber Roof Trusses" published by the Institute for Timber Construction and the Council for Scientific and Industrial Research or as detailed by the designer

Prices for roof trusses and bracing shall include design and preparation of shop drawings

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 6
CARPENTRY & JOINERY (PROVISIONAL)
JM QS

R

<u>The dimensions in the descriptions of the roof construction are nominal and actual measurements are to be obtained from the Representative/Agent and/or the site before design or fabrication of roof trusses commences</u>					
<u>Allow for the preparation and submission of the following documents in respect of all buildings</u>					
1	Detailed shop drawings indicating truss sizes, truss positions, bracings, details, etc. to be submitted for approval prior the commencement of any fabrication		Item		
2	Design certificate indicating the licensed programme used, SABS specifications adhered to, general procedures and loadings adopted, sizes and grading of timber components, details, etc.		Item		
3	Erection guarantee certificate after the whole completed roof truss structure have been inspected, all defective work have been taken out and made good, etc. to the full satisfaction of the Principal Agent		Item		
<u>ROOF TRUSS CONSTRUCTION</u>					
4	Roof construction, mono-pitch roof truss complete as a full set with and including trusses, beams, battens and purlins, measured flat (See Architectural drawings) - Main House Roofs	m2	659		
<u>SUNDRIES</u>					
<u>Sawn Softwood (Grade 5)</u>					
5	38 x 114mm wall plates	m	147		
<u>WOOD PRESERVATIVE</u>					
6	Two coats wood preservative applied hot on wrought exposed roof timbers	m2	493		
<u>FACIAS, BARGE BOARDS, ETC:</u>					
Carried to Summary				R	
Section No. 2 BUILDING WORKS Bill No. 6 CARPENTRY & JOINERY (PROVISIONAL) JM QS					

[illegible]

17 Door size 813 x 2348mm

No

12

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 6
CARPENTRY & JOINERY (PROVISIONAL)
JMQS

R

<p>Section No. 2</p> <p>Bill No. 6</p> <p>CARPENTRY & JOINERY (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	44			
	45			
	46			
	47			
	48			

Carried Forward to Summary of Section No. 2

Section No. 2
BUILDING WORKS
Bill No. 6
CARPENTRY & JOINERY (PROVISIONAL)
JMQS

R

BILL No. 7

CEILINGS, PARTITIONS AND ACCESS FLOORING

PREAMBLES

For preambles see " Specification of materials and methods to be used - PW 371" as published by the National Department of Public Works

Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to

Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.

SUPPLEMENTARY PREAMBLES

Descriptions

Items described as "nailed" shall be deemed to be fixed with hardened steel nails or pins or shot pinned to brickwork or concrete

Items described as "plugged" shall be deemed to include screwing to fibre, plastic or metal plugs at not exceeding 600mm centres, and where described as "bolted", the bolts are measured elsewhere

Proprietary suspended ceilings

Electric light fittings, diffusers, panels, etc generally are "lay in" units of the same dimensions as the suspension grid described and allowance shall be made accordingly for their support, inclusive of any flexibility in setting out that may be required (ceiling panels have not been deducted and pricing shall take cognisance thereof)

Carried to Summary

R

Section No. 2

BUILDING WORKS

Bill No. 7

CEILING, PARTITIONINGS, ETC (PROVISIONAL)

JMQS

User note: The above note shall be included in the bills of quantities after confirmation of the basic design of the ceilings, lighting, air conditioning, etc

"Rhino-Drywall" partition systems

"Rhino-Drywall" partitions shall comprise 63,5mm top and bottom galvanised steel tracks with 63,5mm galvanised steel vertical studs at maximum 600mm centres, friction fitted or pop-riveted to the top and bottom tracks with similar additional vertical studs as necessary at abutments, ends, etc and covered as described with wallboard screwed to studding with "Drywall" screws at maximum 220mm centres. Boards shall be butt jointed and finished with "Rhino" tape and "Readymix D" jointing compound all in accordance with the manufacturer's instructions, complete with flat section aluminium skirtings. Intersections and abutments are measured separately and descriptions shall be deemed to include any additional studs, corner beads, jointing compound

Note: Wall paper and/or paint and varnish finishes are measured elsewhere

User note: Alternatively, wallpaper may be included in the preamble, in which case last-mentioned is not required

INSULATION

"135mm thick flexible non-combustible lightweight Aerolite® insulation material between the roof trusses and over bracing/purlins in a completed roof and ceiling system. Install in accordance with the manufacturers detail and specification. Install Isover 100mm thick Aerolite non-combustible light weight Glasswool thermal ceiling insulation." insulation.

- Climatic zone: Zone 3
- R-value: 2.50m² K/W
- Thermal conductivity: 0.04 W/m²/K.

1	Insulation	m2	523	
---	------------	----	-----	--

NAILED UP CEILINGS

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 7
CEILING, PARTITIONINGS, ETC (PROVISIONAL)
JM QS

R

	<p><u>GYPROC CEILING; 1 x RhinoBoard® 9mm (locally manufactured ISO 9001 & 14001 certification recycled paper content Greentag Level B) fixed to 38 X 38 BRANDERING 450mm centres fixed to tie beam/joist using one line of 2 Gyproc Grabber Screw 32mm. Maximum joist/tie beam spacing is 1200mm. Brander are joined using brander joiners. Fixed using Gyproc Sharp-point Screws 25mm at maximum 150mm centres. Gypframe® UltraSTEEL® Branderling suspended using Gyproc Suspension Bracket at 1200mm centres. Apply Gyproc RhinoTape® to all joints and internal corners. Install Gypframe® Corner Bead to all external corners. Cover Gyproc RhinoTape® with 1 layer of Gyproc RhinoLite® Crestestone® (locally manufactured).</u></p>				
2	<p>Horizontal ceilings, including 38 x 38mm SAP branderling at 400mm centres</p> <p><u>ISOBOARD CEILING; Ceilings to be Isoboard® high density 32-36kg/m³ rigid extruded polystyrene 100% closed cell insulation ceiling formed of 30mm thick x 600mm wide tongue and grooved boards, with IsoPine finish, fixed to trusses under the timber purlins, and edge-fixed with concealed ceiling clips screwed to timber branderling. Boards to be secured to perimeter branderling with drywall screws and washers at 300mm centres.</u></p> <p>• Thickness: 30mm • Board finish: IsoPine.</p>	m2	464		
3	<p>Horizontal ceilings, including 38 x 38mm SAP branderling at 400mm centres</p> <p><u>Cornices</u></p>	m2	59		
4	<p>POLYSTYRENE CORNICE; NMC Decorative Mouldings Wallstyl® FD2 interior polystyrene skirting, size 15 x 110mm high fixed to wall with Adefix® F & W adhesive</p>	m	526		
5	<p>TIMBER CORNICE; 76mm x 19mm SA Pine cornice stop, fixed to wall with 38mm galvanised clout or steel nails at 300mm centres into wall, and to branderling at 400mm centres.</p>	m	70		
Carried to Summary				R	
<p>Section No. 2 BUILDING WORKS Bill No. 7 CEILING, PARTIONINGS, ETC (PROVISIONAL) JMQS</p>					

SUNDRIES

- 6 Extra over gypsum plasterboard ceiling for hinged pressed metal ceiling trap door size 600 x 600mm including all necessary ironmongery and 38 x 38mm SA Pine brace frame

No

8

Carried to Summary

R

Section No. 2
BUILDING WORKS
Bill No. 7
CEILING, PARTITIONINGS, ETC (PROVISIONAL)
JMQS

<p>Section No. 2</p> <p>Bill No. 7</p> <p>CEILING, PARTIONINGS, ETC (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	50			
	51			
	52			
	53			
<p style="text-align: right;">Carried Forward to Summary of Section No. 2</p>			R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 7</p> <p>CEILING, PARTIONINGS, ETC (PROVISIONAL)</p> <p>JMQS</p>				

[illegible]

[illegible]

[illegible]

<p>Section No. 2</p> <p>Bill No. 8</p> <p>IRONMONGERY (PROVISIONAL)</p> <p><u>SUMMARY</u></p>			
Total Brought Forward from Page No.	Page No		Amount
	55		
	56		
	57		
Carried Forward to Summary of Section No. 2			R
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 8</p> <p>IRONMONGERY (PROVISIONAL)</p> <p>JMQS</p>			

Section No. 2

Bill No. 9

STRUCTURAL STEEL

SUMMARY

Total Brought Forward from Page No.

Page
No

59

60

Amount

Carried Forward to Summary of Section No. 2

Section No. 2

BUILDING WORKS

Bill No. 9

STRUCTURAL STEEL

JMQS

R

BILL No. 10

METALWORK

PREAMBLES

For preambles see " Specification of materials and methods to be used - PW 371" as published by the National Department of Public Works

Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to

Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.

SUPPLEMENTARY PREAMBLES

Descriptions of bolts shall be deemed to include nuts and washers. Descriptions of expansion anchors and bolts and chemical anchors and bolts shall be deemed to include nuts, washers and mortices in brickwork or concrete. Metalwork described as "holed for bolt(s)" shall be deemed to exclude the bolts unless otherwise described.

STEEL HANDRAILS, BALUSTRADES, ETC

1000mm high stainless steel by specialist.
Balustrades not to exceed 100mm c/c

1	Balustrades to balconies as per Architect's drawings	m	32
2	Balustrades to raking stairs and landings as per Architect's drawings	m	40

WELDED SCREENS, GATES, ETC

Carried to Summary

R

Section No. 2

BUILDING WORKS

Bill No. 10

METALWORK (PROVISIONAL)

JMQS

The following in framed and welded mild steel purpose made security grille gate and fixing in position complete

3	Pedestrian single gate complete as per Architect's drawings	No	2
4	V-lite aluminium shutter Bi-Fold complete as per Architect's drawings, size 4800 x 2400mm high	No	4
5	Single gate 855 x 2185mm high with frame of 50 x 25 x 1.6mm tubular section framed surround, mitred and welded at angles, gate formed of 25 x 25 x 1.6mm tubular section frame in two sections welded together, each section with two 25 x 25 x 1.6mm tubular section horizontal middle rails and all panels filled in with expanded mesh on inside of openings and with 10 x 10mm mild steel solid section beads on both sides of expanded metal, the frame bolted to wall with eight M10 x 80mm expansion bolts and fitted with four suitable hinges welded to gate and frame and gate supplied with lockable sliding bolt with keep welded to frame (padlock elsewhere)	No	3

ALUMINIUM WINDOWS, DOORS, SHOP FRONTS, ETC

Carried to Summary

R

Section No. 2
BUILDING WORKS
Bill No. 10
METALWORK (PROVISIONAL)
JM QS

Aluminium frames with glazing as required by SANS part N complete with glazing and ironmongery as per Architect's drawings and fixed to brickwork or concrete as per manufacturer's specification, with and including Silicon inside and outside.

Fire Rating to Fire Engineers Specification

AAAMSA certified as to performance, glazing, surface finishing, hardware, fasteners, product certification and, when required, energy rating. anodising: SANS 999.

Powder coating: SANS 1796, minimum thickness for all areas: 0,06 mm.

SANS 10155 Accuracy in Buildings.

Sealing: All corners mitred to form close joints, fixed with stainless self tapping screws to AAMSA standards. All aluminium joints to be sealed 100%. Whole unit to be sealed with silicon, after installation. Seal with matching silicone sealer between the aluminium and building structure, to be airtight. Contractors shall allow for a maximum 10x10mm fillet of clear silicone sealant to the external perimeter of all window units.

Colour: Charcoal

Doors and Windows

6	W1 - 1500 x 600mm high	No	8
7	W2 - 2100 x 600mm high	No	8
8	W3 - 1200 x 1800mm high	No	1
9	W4 - 900 x 1800mm high	No	1
10	W5 - 1200 x 600mm high	No	4

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 10
METALWORK (PROVISIONAL)
JMQS

R

11	W6 - 900 x 1200mm high	No	3		
12	W7 - 400 x 1500mm high	No	1		
13	W8 - 3000 x 2380mm high	No	4		
14	W9 - 1800 x 600mm high	No	4		
15	W10 - 3600 x 1200mm high with aluminium sliding window shutters	No	8		
16	W11 - 900 x 900mm high	No	1		
17	W12 - 1000 x 1000mm high	No	1		
18	W13 - 600 x 600mm high	No	1		
19	D1 - Size 1200 x 2380mm high	No	4		
20	D4 - Size 900 x 2380mm high with 600 x 900mm high window	No	4		
21	D5 - Size 4800 x 2380mm high	No	4		
	<u>Aluminium windows with burglar bars, 15 x 15mm solid aluminium security bars, screws fixed to aluminium window frame @ 200mm c/c max. To opening section only. Colour Charcoal.</u>				
22	W1 - 1500 x 600mm high	No	4		
23	W2 - 2100 x 600mm high	No	2		
24	W3 - 1200 x 1800mm high	No	1		
25	W4 - 900 x 1800mm high	No	1		
26	W5 - 1200 x 600mm high	No	4		
27	W6 - 900 x 1200mm high	No	4		
Carried to Summary					
Section No. 2 BUILDING WORKS Bill No. 10 METALWORK (PROVISIONAL) JMQS					R

[illegible]

<p>Section No. 2</p> <p>Bill No. 10</p> <p>METALWORK (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	62			
	63			
	64			
	65			
	66			
Carried Forward to Summary of Section No. 2			R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 10</p> <p>METALWORK (PROVISIONAL)</p> <p>JMQS</p>				

Mix

Granolithic shall attain a compressive strength of at least 41MPa. The coarse aggregate shall comply with SABS 1083 and be capable of passing a 10mm mesh sieve. Where the thickness of the granolithic exceeds 25mm, the size of the coarse aggregate shall be increased to the maximum size compatible with the thickness of the granolithic

Panels

Granolithic shall be laid in panels not exceeding 14m² for granolithic finishes, not exceeding 9,5m² for bonded finishes and not exceeding 6m² for all external granolithic. Wherever possible, panels shall be square but at no time should the length of the panel exceed 1,5 times its width. Joints between panels shall be positioned, where possible, over joints in the floor slab and shall be at least 3mm wide through the full thickness of the finish, separated by strips of wood or fibreboard and finished with small V-joints

Laying

Monolithic granolithic shall be applied to the partially set slab and thoroughly compacted and lightly wood floated to the required levels

Bonded granolithic shall be applied to the slab after applying a 1:1 sand and cement slurry brushed over the surface and allowed to partially set before applying the granolithic, thoroughly compacted and lightly wood floated to the required levels

After wood floating, the monolithic and bonded granolithic shall remain undisturbed until bleeding has ceased and the surface has stiffened, any remaining bleed water and laitance shall then be removed and the surface steel trowelled or power floated

Curing, seasoning and protection

Granolithic shall be covered with clean hessian with waterproof building foil over and kept wet for at least seven days after laying

Carried to Summary

Section No. 2
BUILDING WORKS
Bill No. 11
PLASTERING (PROVISIONAL)
JMQS

R

[illegible]

	<u>One coat 1:5 cement plaster on brickwork finished with steel trowel, 12-15mm thick. CEMENT PLASTERED CEILING: All exposed concrete ceilings to be cleaned properly, slushed with a 1:2 river sand/cement mixture. Slushing to be cured properly before applying 1:5 cement plaster finish with a fine woodfloat. smooth concrete surfaces must be chipped before slush is applied.</u>				
8	On soffits of concrete slabs	m2	611		
	<u>Cement plaster rendering coat with gypsum skim plasterfinishing coat, on brickwork</u>				
9	On walls	m2	3 115		
10	On soffits of concrete slab	m2	502		
11	On narrow widths	m2	92		
	<u>Plaster the entire ceiling with 3 to 6mm lightweight hemi-hydrate gypsum plaster the same day the board has been erected.</u>				
12	On gypsum board ceilings	m2	537		
	<u>EXTERNAL PLASTER</u>				
	<u>One coat 1:4 cement plaster on brickwork finished with steel trowel, 12-15mm thick</u>				
13	On soffits of slabs	m2	109		
Carried to Summary					
Section No. 2 BUILDING WORKS Bill No. 11 PLASTERING (PROVISIONAL) JMQS					R

<p>Section No. 2</p> <p>Bill No. 11</p> <p>PLASTERING (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	68			
	69			
	70			
	71			

Carried Forward to Summary of Section No. 2

R

Section No. 2
BUILDING WORKS
Bill No. 11
PLASTERING (PROVISIONAL)
JMQS

Section No. 2
BUILDING WORKS
Bill No. 12
TILING (PROVISIONAL)
JMQS

3	Circular cutting	m	9		
	<u>FLOOR TILING</u>				
	<u>Internal floor tiles (PC sum R250.00/m² for supply and delivery, store, waste, excluding labour and VAT) fixed adhesive to bedding (bedding elsewhere) and flush po with tinted jointing compound</u>				
4	To floors and landings with joints continuous in both directions	m2	707		
5	To stairs	m2	38		
6	Skirting 100mm high tile skirting	m	703		
	<u>External floor tiles (PC sum R250.00/m² for supply and delivery, store, waste, excluding labour and VAT) fixed adhesive to bedding (bedding elsewhere) and flush po with tinted jointing compound</u>				
7	To floors and landings with joints continuous in both directions	m2	288		
8	to steps	m2	73		
9	Skirting 100mm high tile skirting	m	330		
	<u>SUNDRIES</u>				
10	50 x 50 x 2mm thick natural anodised angle set aluminium to skirting	m	330		
11	Stainless steel tile-in corner protector 30 x 30 x 10mm brushed finish	m	5		
12	Aluminium angle edges with suitable flexible infill, brass	m	16		
13	External aluminium straight edge as by KIRK Marketing (Code: 686) or similar approved	m	29		
	Carried to Summary			R	
	Section No. 2				
	BUILDING WORKS				
	Bill No. 12				
	TILING (PROVISIONAL)				
	JMQS				

[illegible]

<p>Section No. 2</p> <p>Bill No. 12</p> <p>TILING (PROVISIONAL)</p> <p><u>SUMMARY</u></p>			
Total Brought Forward from Page No.	Page No		Amount
	73		
	74		
	75		
Carried Forward to Summary of Section No. 2			R
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 12</p> <p>TILING (PROVISIONAL)</p> <p>JMQS</p>			

<u>"Vaal Sanitaryware" or Equal Approved</u>					
7	D-Neo Wall mount Pan - Rimless with soft close seat and cover with and including wall mounted concealed Dura System with white flush plate.	No	13		
8	X-Base Vanity - Graphite Matt, 100cm D-Code Furniture Basin	No	13		
9	D-Code Built in Bathtub supplied with support frame	No	8		
10	Hansgrohe S21 S210-F720 Built-in sink with manual waste set.	No	4		
11	Hansgrohe S71 S719-U450 Stainless Steel Undermount single bowl sink 450	No	4		
12	Hansgrohe Vernis Shape Overhead Shower 230 x 170mm, 1 Jet EcoSmart with ball joint adjustable spray - chrome finish	No	8		
<u>"Franke" or Equal Approved</u>					
13	Franke 0,8mm Grade 403 17/10 stainless steel ET103 mini wash trough (Code: 2560007), size 540 x 370 x 240mm deep with sloped front, wash ridges and 40mm waste outlet, fixing lugs (elsewhere measured)SS.	No	4		
14	Franke 0,8mm Grade 403 17/10 stainless steel ET102 double wash trough (Code: 2560005), size 1030 x 430 x 348mm deep with sloped front, wash ridges and 40mm waste outlet, fixing lugs (elsewhere measured)	No	4		
<u>Taps, Waste, Traps, etc</u>					
15	Logis single lever basin mixer 110 fine with and including Hansgrohe chrome waste set push-open for basin and bidet mixers, cup-shaped trap standard model	No	13		
16	Hansgrohe Logis Chrome Single lever bath mixer for concealed installation with and including Hansgrohe Chrome Crometta Shower holder set 100 1 jet EcoSmart with shower hose 125cm, Hansgrohe Exafill finish set bath filler and Hansgrohe Waste set push-open for bathtubs	No	8		
Carried to Summary				R	
Section No. 2					
BUILDING WORKS					
Bill No. 13					
PLUMBING AND DRAINAGE (PROVISIONAL)					
JMQS					

[illegible]

<p>Section No. 2</p> <p>Bill No. 13</p> <p>PLUMBING AND DRAINAGE (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	77			
	78			
	79			
<p style="text-align: right;">Carried Forward to Summary of Section No. 2</p>			R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 13</p> <p>PLUMBING AND DRAINAGE (PROVISIONAL)</p> <p>JMQS</p>				

[illegible]

PAINT ON PLASTERED WALLS

Prepare and applying one coat of Professional Gypsum and Plaster Primer (PP 700) to achieve a continuous film (allow 16 hours to dry) and finish with two coats of Plascon Double Velvert (VEL/TDV) to achieve complete obliteration (allowing 2 hours drying between coats). Colour to Architect's specifications

1	On internal plastered walls	m2	3 207
---	-----------------------------	----	-------

SMOOTH CONCRETE SURFACES WITH

Prepare and apply one coat of Professional Gypsum and Plaster Primer (PP 700) to achieve a continuous film (allow 16 hours to dry) finish Coats: Apply two full coats of Plascon Professional Super Matt (PEM 900/TSA) to achieve complete obliteration (allowing 1 hour drying between coats)

2	On plastered ceilings and slab edges	m2	611
---	--------------------------------------	----	-----

ON PLASTERBOARD, ETC

Prepare and apply ne coat of Professional Gypsum and Plaster Primer (PP 700) to achieve a continuous film (allow 16 hours to dry) and finish with two full coats of Plascon Professional Super Matt (PEM 900/TSA) to achieve complete obliteration, allowing 1 hour drying between coats

3	On ceilings including cornices	m2	537
---	--------------------------------	----	-----

ON FIBRE-CEMENT

Preparing, priming nailheads and cover strips with primer, filling and applying one universal undercoat and two coats exterior quality 'Plascon Super Acrylic PVA' paint

4	On fascias and barge boards	m2	67
---	-----------------------------	----	----

5	On sills	m2	132
---	----------	----	-----

METAL SURFACES WITH

Carried to Summary

R

Section No. 2
BUILDING WORKS
Bill No. 15
PAINTWORK (PROVISIONAL)
JMQS

Prepare and apply one coat of Plascon Metal Primer (UC 170) to achieve a continuous film (allow 36 hours to dry) and finish with two full coats of Plascon Water based Velvagio (VLW/TVW) to achieve complete obliteration (allowing 4 hours drying between coats)

NB: if white is used, three coats might be necessary to achieve obliteration.

6	Gates, grilles, burglar screens, balustrades, etc (both sides measured over the full flat area)	m2	15	
---	---	----	----	--

WOOD SURFACES WITH

Prepare and apply with 1 coat primer, 1 coat universal undercoat and finish with coats: 2 coats superior quality eggshell enamel or similar approved. Colour to Architects Specification or White

7	On doors	m2	169	
---	----------	----	-----	--

8	On door frames	m2	32	
---	----------------	----	----	--

9	On skirtings, rails, etc not exceeding 300 mm girth	m	330	
---	---	---	-----	--

Carried to Summary

R

Section No. 2
BUILDING WORKS
Bill No. 15
PAINTWORK (PROVISIONAL)
JM QS

<p>Section No. 2</p> <p>Bill No. 15</p> <p>PAINTWORK (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	82			
	83			
	84			
<p style="text-align: right;">Carried Forward to Summary of Section No. 2</p>			R	
<p>Section No. 2</p> <p>BUILDING WORKS</p> <p>Bill No. 15</p> <p>PAINTWORK (PROVISIONAL)</p> <p>JMQS</p>				

Bill No	SUMMARY - BUILDING WORKS	Page No	Amount	
			R	c
1	FOUNDATIONS (PROVISIONAL)	24		
2	CONCRETEWORK, FORMWORK & REINFORCEMENTS (PROVISIONAL)	29		
3	MASONRY (PROVISIONAL)	36		
4	WATERPROOFING (PROVISIONAL)	40		
5	ROOF COVERING (PROVISIONAL)	43		
6	CARPENTRY & JOINERY (PROVISIONAL)	49		
7	CEILING, PARTITIONINGS, ETC (PROVISIONAL)	54		
8	IRONMONGERY (PROVISIONAL)	58		
9	STRUCTURAL STEEL	61		
10	METALWORK (PROVISIONAL)	67		
11	PLASTERING (PROVISIONAL)	72		
12	TILING (PROVISIONAL)	76		
13	PLUMBING AND DRAINAGE (PROVISIONAL)	80		
14	GLAZING (PROVISIONAL)	81		
15	PAINTWORK (PROVISIONAL)	85		
Total Carried to Final Summary			R	
Section No. 2 BUILDING WORKS JMQS				

Item No	Quantity	Rate	Amount
<u>BILL NO. 1</u>			
<u>GENERAL SITE WORKS, ETC (PROVISIONAL)</u>			
<u>PREAMBLES</u>			
For preambles see "Specification of materials and methods to be used - PW 371" as published by the National Department of Public Works			
Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to.			
Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.			
<u>SUPPLEMENTARY PREAMBLES</u>			
<u>Supplementary preambles and full descriptions of materials, items, work, etc. applicable to Section No. 3</u>			
Earthworks are to be carried out in accordance with SABS 1200D subjected to the following amendments:			
<ol style="list-style-type: none"> 1. the degree of accuracy shall be Degree II 2. the finished level tolerance in sub clause (B3) of SABS 1200D to be amended to read $\pm 25\text{mm}$ 			
Carried to Summary			
Section No. 3			R
EXTERNAL WORKS			
Bill No. 1			
BULK EARTHWORKS (PROVISIONAL)			
JMQS			

Welded Mesh Medium Security Fence must comply to the following:

- As per PW371-A Edition 2.0
- ISO 9001 accreditation
- SANS 10244-2
- Min 10 years anti corrosion guarantee
- Shop drawings for both gates and panels to be submitted to the PA prior to fixing for approval
- Certificate of compliance for material and installation to be issued by the manufacture and/or engineer

SITE CLEARANCE

Site clearance

1	Digging up and removing rubbish, debris, vegetation, hedges, shrubs and trees not exceeding 200mm girth, bush, etc. Topsoil to be stockpiled off site and a portion retained for backfilling behind kerbs and for grassed areas	m2	1 285	
---	---	----	-------	--

Taking out and removing, grubbing up roots and filling in holes

2	Tree or stump exceeding 500mm and not exceeding 1000mm girth	No	5	
3	Tree or stump exceeding 1000mm and not exceeding 1500mm girth	No	5	

BULK EARTHWORKS AND PLATFORMS

Compaction of surfaces (rip and scarify)

4	Compaction of ground surface under roads and parking areas including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 93% Mod AASHTO density	m2	1 285	
---	--	----	-------	--

Carried to Summary

R

Section No. 3
EXTERNAL WORKS
Bill No. 1
BULK EARTHWORKS (PROVISIONAL)
JMQS

	<u>Open face excavation in all materials to form platforms/terraces in earth over sloping site</u>				
5	Open face excavation	m3	2 956		
	<u>Extra over excavation for:</u>				
6	Soft rock	m3	1 478		
7	Hard rock	m3	1 478		
	<u>Extra over all excavations for carting away</u>				
8	Extra over all excavations for carting away surplus material from excavations and/or from stockpiles on site to a dumping site to be located by the Contractor	m3	2 956		
	<u>Selected filling of G6 material supplied by the contractor compacted in layers of 150mm to 95% MOD AASHTO density</u>				
9	Over site to form platforms	m3	3 308		
	<u>Selected filling of G5 material (CBR>15) supplied by the contractor compacted to 98% MOD AASHTO density</u>				
10	Over site to form platforms	m3	386		
	<u>Compaction of surfaces (rip and scarify)</u>				
11	Compaction of ground surface under floors etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 95% MOD AASHTO density	m2	1 285		
	<u>Prescribed density tests on filling</u>				
12	Modified AASHTO Density test	No	22		
Carried to Summary				R	
Section No. 3 EXTERNAL WORKS Bill No. 1 BULK EARTHWORKS (PROVISIONAL) JMQS					

<p>Section No. 3</p> <p>Bill No. 1</p> <p>BULK EARTHWORKS (PROISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	87			
	88			
	89			

Carried Forward to Summary of Section No. 3

Section No. 3
EXTERNAL WORKS
Bill No. 1
BULK EARTHWORKS (PROISIONAL)
JMQS

R

Welded Mesh Medium Security Fence must comply to the following:

- As per PW371-A Edition 2.0
- ISO 9001 accreditation
- SANS 10244-2
- Min 10 years anti corrosion guarantee
- Shop drawings for both gates and panels to be submitted to the PA prior to fixing for approval
- Certificate of compliance for material and installation to be issued by the manufacture and/or engineer

BOUNDARY WALL

Excavation

Excavate in earth not exceeding 2m deep below natural, elevated or reduced ground level for

1	Trenches	m3	223		
---	----------	----	-----	--	--

Sundries

Extra over trench and hole excavations in earth for excavation in

2	Extra over excavations in earth for trenches and holes for excavations in soft rock	m3	112		
---	---	----	-----	--	--

3	Extra over excavations in earth for trenches and holes for excavations in hard rock	m3	112		
---	---	----	-----	--	--

Extra over all excavations for carting away

4	Extra over all excavations for carting away surplus material from excavations and/or from stockpiles on site to a dumping site to be located by the Contractor	m3	151		
---	--	----	-----	--	--

Risk of collapse of excavations

5	Risk of collapse of sides of excavations for trenches and holes from natural, elevated or reduced ground level to not exceeding 1,5m deep	m2	494		
---	---	----	-----	--	--

Carried to Summary

R

Section No. 3

EXTERNAL WORKS

Bill No. 2

BOUNDARY WALL AND FENCING WORKS (PROVISIONAL)

JMQS

	<u>Keeping excavations free of water</u>			
6	Allow for keeping excavations free of all water other than subterranean water		Item	
	<u>Filling, etc.</u>			
7	Backfilling from the excavations to trenches and holes compacted to 90% modified AASHTO density	m3	75	
8	Imported earth filling supplied by the Contractor and brought onto site, under floors, steps, pavings, etc. compacted to 95% modified AASHTO density	m3	72	
	<u>Compaction of surfaces</u>			
9	Compaction of ground surface under trenches, holes etc including scarifying for a depth of 150mm, breaking down oversize material, adding suitable material where necessary and compacting to 93% Mod AASHTO density	m2	146	
	<u>Prescribed density tests on filling</u>			
10	Tests to determine the degree of compaction, etc. of ground or filling	No	10	
	<u>Protection against termites</u>			
11	To bottoms and sides of trenches, bases, etc	m2	640	
	<u>Reinforced concrete</u>			
	<u>30MPa/20mm concrete</u>			
12	In footings to walls cast against excavated surfaces, stepped and levelled	m3	40	
	<u>Test cubes</u>			
13	Prepare set of three 150 x 150 x 150mm concrete strength test cubes, label and send to an approved laboratory for testing, pay all charges and submit report to the Representative/Agent. Only successful tests will be paid for <u>(Provisional)</u>	No	4	
	Carried to Summary			
	Section No. 3			
	EXTERNAL WORKS			
	Bill No. 2			
	BOUNDARY WALL AND FENCING WORKS (PROVISIONAL)			
	JMQS			

<u>Reinforcement</u>					
<u>Steel bar reinforcement to structural concrete work</u>					
14	Various diameter steel reinforcing bars	t	6.16		
<u>Mesh reinforcement</u>					
15	Mesh reinforcement with mesh reference number 617 laid in walls, slab, etc. with 300mm wide side and end laps (measured net)	m2	130		
<u>Masonry</u>					
16	Piers	m3	52		
17	One brick wall	m2	555		
18	330mm cavity brick walls comprising two half brick skins with 115mm wide cavity, complete with and including concrete infill, reinforcement, mesh, brickforce and wall ties as per Architect's and Engineer's drawings	m2	92		
<u>Brick reinforcement</u>					
19	Brick reinforcement 75mm wide built into brick walls with sufficient laps at end joints, angles and intersections (measured net)	m	2 164		
20	Brick reinforcement 150mm wide built into brick walls with sufficient laps at end joints, angles and intersections (measured net)	m	6 527		
<u>Face bricks</u>					
<u>External facings in approved Country Classic Satin face bricks (FBS) pointed with square recessed horizontal and vertical joints</u>					
21	Extra over ordinary brickwork for facing and pointing in stretcher bond	m2	1 014		
22	Brick on edge coping	m	168		
Carried to Summary				R	
Section No. 3 EXTERNAL WORKS Bill No. 2 BOUNDARY WALL AND FENCING WORKS (PROVISIONAL) JM QS					

	<u>Movement joints, etc</u>				
23	Movement joint of 10mm impregnated fibre board built in vertically between brickwork	m2	136		
	<u>Subsoil drainage, etc</u>				
24	Subsoil drainage complete with and including excavations, cart away, filling, concrete stones, bidim, 110mm diameter uPVC perforated pipe, 50mm diameter PVC pipe weep holes, along the fill side of retaining wall as per Engineer's drawings	m	80		
	<u>GATES</u>				
	<u>38 x x25mm slatted MS sliding gate with 30mm spacing between slats, 100 x x50 x 2mm MS square tubing, and gate motor</u>				
25	3000 x 2400mm high vehicular gate with motor	No	1		
Carried to Summary					
Section No. 3 EXTERNAL WORKS Bill No. 2 BOUNDARY WALL AND FENCING WORKS (PROVISIONAL) JMQS					R

Section No. 3

Bill No. 2

BOUNDARY WALL AND FENCING WORKS (PROVISIONAL)

SUMMARY

Total Brought Forward from Page No.

**Page
No**

Amount

91

92

93

94

95

Carried Forward to Summary of Section No. 3

R

Section No. 3

EXTERNAL WORKS

Bill No. 2

BOUNDARY WALL AND FENCING WORKS (PROVISIONAL)

JMQS

Section No. 3
EXTERNAL WORKS
Bill No. 3
PAVING, WALKWAYS AND CARPORTS (PROVISIONAL)
JMQS

	<u>Earth filling supplied by the contractor compacted to 95% Mod. AASHTO density (Selected layer natural gravel, G7)</u>				
4	Under paving etc.	m3	119		
	<u>Earth filling supplied by the contractor compacted to 97% Mod. AASHTO density (Subbase C4 material)</u>				
5	Under paving etc.	m3	119		
	<u>Sand bedding under paving</u>				
6	20mm thick dry, clean, washed riversand layer evenly spread over filling (elsewhere measured), levelled, watered and rammed to receive waterproof membrane (elsewhere measured) under solid floors	m2	792		
	<u>Compaction of surfaces</u>				
7	Compaction of ground surface under floors etc including scarifying for a depth of 200mm, breaking down oversize material, adding suitable material where necessary and compacting to 95% Mod AASHTO density	m2	792		
	<u>Prescribed density tests on filling</u>				
8	"Modified AASHTO Density" test	No	11		
	<u>Approved soil sterilant type weedkiller applied strictly according to label specifications</u>				
9	Under paving etc	m2	792		
	<u>One layer of 250 micron "Consol Plastics Gunplas USB Green" waterproof sheeting sealed at laps with "Gunplas Pressure Sensitive Tape"</u>				
10	Under paving	m2	792		
	<u>Precast concrete block walkways</u>				
	Paving is to be laid in accordance with SABS 1200 MJ, SABS 1058 and the Concrete Masonry Association's specifications				
Carried to Summary				R	
Section No. 3 EXTERNAL WORKS Bill No. 3 PAVING, WALKWAYS AND CARPORTS (PROVISIONAL) JMQS					

Paving is to be laid to herringbone pattern on and including 20mm (thickness after final compaction) clean river sand (preparation of ground or filling elsewhere)

Clean sand is to be swept into joints between roadstones

60mm Coloured "Concor Bondbrick" interlocking paving blocks (25Mpa)

11	Paving to walkways, etc to falls	m2	792		
12	Fair circular cutting	m	7		
13	Kerbs fig. 3 with 150 x 150 x 300mm unreinforced concrete haunching at back of each joint including excavations, backfilling etc	m	221		
	<u>SABS 731-1987 yellow or white roadmark paint on paving at a rate of 1 litre/m2</u>				
14	Line 100mm wide	m	83		
15	Numeral or letter 1250mm high (GM7)	No	12		
16	Traffic arrow 1250 x 500mm wide extreme (G M4.1)	No	8		

CARPOTS WITH ROOF SHEETING TO SLIGHT FALLS

Carried to Summary

R

Section No. 3
EXTERNAL WORKS
Bill No. 3
PAVING, WALKWAYS AND CARPORTS (PROVISIONAL)
JMQS

Carpots comprising the following: concrete foundations for columns to be 20Mpa concrete, 500 x 500 x 600mm deep including all excavations, backfilling, compaction, carting away, etc; columns 76 x 76 x 3mm hot rolled tubing with 150 x 150 x 3mm base plates and 200 x 70 x 6mm top flanges: columns 2600mm minimum height, beams; 76 x 76 x 3mm hot rolled tubing with closed ends; beams bolted to columns with two 10 x 100mm bolts and nuts at each column; purlins; 150 x 75 x 20 x 3mm hot rolled lipped channels bolted to cleats on beams with 0.5mm thick chromadek finished IBR profile roof sheeting; all steelwork cleaned with degreaser and painted with one each of red oxide and universal primer with two coats enamel paint

- 17 Range of carpots (one row) comprising four bays, each bay 2,5 x 5,0m on plan, with carpot structure stepped over sloping site if required, including cutting of existing paving blocks around columns

No

2

Carried to Summary

R

Section No. 3
EXTERNAL WORKS
Bill No. 3
PAVING, WALKWAYS AND CARPORTS (PROVISIONAL)
JM QS

<p>Section No. 3</p> <p>Bill No. 3</p> <p>PAVING, WALKWAYS AND CARPORTS (PROVISIONAL)</p> <p><u>SUMMARY</u></p>			
Total Brought Forward from Page No.	Page No		Amount
	97		
	98		
	99		
	100		
<p style="text-align: right;">Carried Forward to Summary of Section No. 3</p>		R	
<p>Section No. 3</p> <p>EXTERNAL WORKS</p> <p>Bill No. 3</p> <p>PAVING, WALKWAYS AND CARPORTS (PROVISIONAL)</p> <p>JMQS</p>			

Fixing of pipes

Unless specifically otherwise stated, descriptions of pipes shall be deemed to include fixing to walls etc, casting in, building in or suspending not exceeding 1m below suspension level

Reducing fittings

Where fittings have reducing ends or branches they are described as "reducing". In the case of pipes with diameters not exceeding 60mm only the largest end or branch size is given. Should the contractor wish to use other fittings and bushes or reducers he may do so on the understanding that no claim in this regard will be entertained. In the case of pipes with diameters exceeding 60mm all sizes are given and no claim for extra bushes, reducers, etc will be entertained

Exposed concrete surfaces

Exposed surfaces of concrete stormwater channels, cover slabs, inspection eye marker slabs, gulley tops, cleaning eye tops, catchpits, inspection chambers, etc shall be finished smooth with plaster

Excavations

No claim for rock excavation will be entertained unless the contractor has timeously notified the quantity surveyor thereof prior to backfilling

"Soft rock" and "hard rock" shall be as defined in "Earthworks"

Laying, backfilling, bedding, etc. of pipes

Pipes shall be laid and bedded and trenches shall be carefully backfilled in accordance with manufacturers' instructions

Carried to Summary

Section No. 3
EXTERNAL WORKS
Bill No. 4
TANKS AND PUMPS (PROVISIONAL)
JMQS

R

Where no manufacturers' instructions exist pipes shall be laid in accordance with clauses 5.1 and 5.2 of each of the following:
SANS 1200 L : Medium-pressure pipelines
LD : Sewers
LE : Stormwater drainage
Pipe trenches etc shall be backfilled in accordance with clauses 3, 5.5, 5.6, 5.7 and 7 of SANS 1200
DB : Earthworks (Pipe trenches)
Pipes shall be bedded in accordance with clauses 3.1 to 3.4.1, 5.1 to 5.3 and 7 of SANS 1200
LB : Bedding (Pipes).
Unless otherwise described bedding of rigid pipes shall be class B bedding

Holes for pipes

Holes for pipes, cutting and fitting around pipes, the making good thereof, etc. in brick and/or concrete sidewalls of catch pits, manholes, valve chambers, etc. shall be deemed to be included in descriptions of pipework

Tendered rates must make provision for this as no additional claims in this regard will afterwards be entertained

Mixing of concrete

No hand mixing of concrete will be allowed on site

Structural steel

Descriptions of bolts shall be deemed to include nuts and washers

Descriptions of L-shaped and U-shaped anchor bolts shall be deemed to include bending, threading, nuts and washers and embedding in concrete

All structural steel to be painted with one coat red oxide metal primer before delivery to site

Carried to Summary

Section No. 3
EXTERNAL WORKS
Bill No. 4
TANKS AND PUMPS (PROVISIONAL)
JMQS

R

<u>BOREHOLE & TREATMENT PLANT</u>					
1	Drilling and equipping of borehole with and including water purification/treatment plant		Item		600 000.00
<u>TANKS, STANDS AND PUMPS</u>					
<u>Tank Plinth</u>					
<u>Excavation</u>					
<u>Excavate in earth not exceeding 2m deep below natural, elevated or reduced ground level for</u>					
2	Trenches	m3	6		
<u>Sundries</u>					
<u>Extra over trench and hole excavations in earth for excavation in</u>					
3	Extra over excavations in earth for trenches and holes for excavations in soft rock	m3	1		
4	Extra over excavations in earth for trenches and holes for excavations in hard rock	m3	1		
<u>Extra over all excavations for carting away</u>					
5	Extra over all excavations for carting away surplus material from excavations and/or from stockpiles on site to a dumping site to be located by the Contractor	m3	6		
<u>Risk of collapse of excavations</u>					
6	Risk of collapse of sides of excavations for trenches and holes from natural, elevated or reduced ground level to not exceeding 1,5m deep	m2	7		
<u>Keeping excavations free of water</u>					
7	Allow for keeping excavations free of all water other than subterranean water		Item		
Carried to Summary				R	
Section No. 3					
EXTERNAL WORKS					
Bill No. 4					
TANKS AND PUMPS (PROVISIONAL)					
JM QS					

[illegible]

<u>1800mm high Poly 6000 coated clearvu fencing, using 3mm and 4mm wire around Tanks and Pumps</u>			
15	Fencing	m	16
16	Single gate 1,5m wide	No	1
<u>Pumps</u>			
17	Two CR3-10 pumps with 2.2kW motors connected in parallel (one pump on standby) mounted on a common base with pump able to deliver a flow of 0.5l/s at three fire hose reels (total 1.5l/s) at a maximum pressure of 300kPa, installed complete with pressure gauge, control panel, electrical installation, 50mm flanged connections, etc	No	1
<u>Elevated tanks and stands</u>			
18	Supply and installation of 10 000 "Jojo or similar approved" water tank complete including all excavations, concrete bases, plinths and slabs, 9m elevated steel platform, pipework, fittings, valves, connections, sterilization of tank, etc, all as per Engineer and Architect's drawings	No	4
Carried to Summary			R
Section No. 3 EXTERNAL WORKS Bill No. 4 TANKS AND PUMPS (PROVISIONAL) JMQS			

<p>Section No. 3</p> <p>Bill No. 4</p> <p>TANKS AND PUMPS (PROVISIONAL)</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	102			
	103			
	104			
	105			
	106			
	107			

Carried Forward to Summary of Section No. 3

Section No. 3
EXTERNAL WORKS
Bill No. 4
TANKS AND PUMPS (PROVISIONAL)
JMQS

R

Bill No		Page No	Amount R	c
1	BULK EARTHWORKS (PROISIONAL)	90		
2	BOUNDARY WALL AND FENCING WORKS (PROVISIONAL)	96		
3	PAVING, WALKWAYS AND CARPORTS (PROVISIONAL)	101		
4	TANKS AND PUMPS (PROVISIONAL)	108		
Total Carried to Final Summary			R	
Section No. 3 EXTERNAL WORKS JMQS				

Specification and drawings

Tenderers are referred to the Electrical Specification and drawings annexed to these bills of quantities for full descriptions of the project specification, materials to be used, etc

Note: All items shall be priced for whatever cost may be considered necessary for Preliminary and General items to carry out the Electrical Installation in full, as detailed in the drawings, Specifications and Schedules, which shall include, but shall not be limited, to the following:

Site establishment and de-establishment - including but not limited to latrines, water, generators, fuel, all safety aspects, site office, etc.

Providing site information to the Engineer upon request, marking up of drawing during construction and compiling of As-built drawings

Electrical Certificate of Compliance (COC) for the entire installation

Coding and Labelling of all plant and equipment, including cables and distribution boards

CABLING

Wiring with the following sizes of insulated copper conductor single core/multi strand cable in surface/recessed PVC conduit as required.

All distances are to be confirmed by the contractor from the drawings provided and from site inspections.

The contractor is to use SABS approved components.

All cables shall be compliant to SANS 1507-3 requirements and recommendations

Carried to Summary

Section No. 4
ELECTRICAL ENGINEERING WORKS
Bill No. 1
ELECTRICAL WORKS (PROVISIONAL)
JMQS

R

All prices in this Section are required to exclude trenching (trenching is included in Section 3 of this bill)

Bare copper earth conductors laid with cable in trenches or sleeve pipes and bonded to cables with plastic strapping at 2m centres

2.5mm² general purpose wire, as indicated on the schematic diagrams for light circuits (Red, Black & Insulated Earth)

1	- Supply	m	2 500
2	- Install	m	2 500

4 mm² general purpose wire, as indicated on the schematic diagrams for power outlets , plugs, brick lights, and mechanical units(Red, Black & Insulated Earth)

3	- Supply	m	7 000
4	- Install	m	7 000

6mm² general purpose wire, as indicated on the schematic diagrams for the stoves (Red, Black & Insulated Earth)

5	- Supply	m	400
6	- Install	m	400

4 mm² 1-phase 3-core Cu PVC SWA single phase cable compatible with SANS 1507-3 for exterior lights parking lights and to refuse area, including junction boxes, cable termination and connections

7	- Supply	m	150
8	- Install	m	150

Carried to Summary

R

Section No. 4
ELECTRICAL ENGINEERING WORKS
Bill No. 1
ELECTRICAL WORKS (PROVISIONAL)
JMQS

[illegible]

The Contractor shall apprise himself of all existing services and make sure that these services are not damaged during excavations

Cables may not be covered before the Consulting Engineer has inspected and approved the cables and trenches. If the Contractor disregards this requirement the trenches may be re-opened at the discretion of the Consulting Engineer at the Contractor's expense.

Concrete cable markers shall be introduced at the beginning and at the end of each cable route (for example, where a cable enters a distribution kiosk or a building), at changes in direction, at all joints and above the entrance and exit of cable sleeves along the entire route of the cable at intervals not exceeding 50 m.

19	- Supply	No	4		
20	- Install	No	4		
<u>Power Cable Manhole - FC chamber, with bases, ports and a concrete coverslab with a hinged DMC polymer lid which is lockable including excavation of dimensions 1m wide x 1m wide x 800mm deep</u>					
21	- Supply	No	5		
22	- Install	No	5		
<u>Data Sleeve Manhole - FC chamber, with bases, ports and a concrete coverslab with a hinged DMC polymer lid which is lockable including excavation of dimensions 600mm wide x 600mm wide x 600mm deep</u>					
23	- Supply	No	1		
24	- Install	No	1		
25	Excavation for Power Cable and Data Sleeves (500mm wide x 700mm deep) in earth for cable trenches, backfilling of trenches with 150mm of soft sifted bedding material	m3	60		

Carried to Summary

R

Section No. 4
ELECTRICAL ENGINEERING WORKS
Bill No. 1
ELECTRICAL WORKS (PROVISIONAL)
JMQS

[illegible]

The type of conduit and accessories shall be of the non-metallic type where chased into the wall but metallic type Bosal for within the roof space

For lighting circuits and socket outlets, the conduit used shall have an external diameter of 20mm

For data points, the conduit used shall have an external diameter of 25mm

M20 PVC conduit complete with hangers, anchors, nuts and bolts, bends, tees, elbows, junction boxes, clamps, fittings and end caps, chased 50mm wide x 40mm deep and make good - to be chased into wall and installed in floor

32	- Supply	m	3 000
----	----------	---	-------

33	- Install	m	3 000
----	-----------	---	-------

M20 PVC conduit round boxes with lid and screws (1-way, 2-way, 3-way, 4-way, back and side entry as required)

34	- Supply	No	200
----	----------	----	-----

35	- Install	No	200
----	-----------	----	-----

M25 PVC conduit complete with hangers, anchors, nuts and bolts, bends, tees, elbows, junction boxes, clamps, fittings and end caps for wiring in the the roof space

36	- Supply	m	2 000
----	----------	---	-------

37	- Install	m	2 000
----	-----------	---	-------

M25 PVC conduit round boxes with lid and screws (1-way, 2-way, 3-way, 4-way, back and side entry as required)

38	- Supply	No	20
----	----------	----	----

39	- Install	No	20
----	-----------	----	----

Carried to Summary

R

Section No. 4
ELECTRICAL ENGINEERING WORKS
Bill No. 1
ELECTRICAL WORKS (PROVISIONAL)
JMQS

<u>1.6mm galvanised Draw Wire in all conduit and sleeves, including data sleeves and data conduit</u>				
40	- Supply	m	5 500	
41	- Install	m	5 500	
<u>DATA INSTALLATION</u>				
<u>32mm sleeves for data cables are covered in and Section 6 of this bill.</u>				
<u>Conduit is required to be run with a draw wire to each telephone/data point terminating in a round conduit box.</u>				
<u>300mmx300mm Flush mounted Data/Telephone distribution board with metal tray, architrave frame and hinged doors and shall be flush mounted - 20mm thick soft wooded panel (fine grade pine to SANS 1359)</u>				
42	- Supply	No	5	
43	- Install	No	5	
44	Allow for provisional amount of R181 818,180for application and connection fee for new internet fibre connection with approved service provider		Item	181 818.18
45	Add for profit			%
46	Add for general attendance			%
<u>LIGHTING & SWITCHES</u>				
<u>LIGHT FITTINGS</u>				
<u>All cover plates must be secured with two sunken-chromed vandal proof screws.</u>				
<u>Where not specfied below, lamps to have a lifespan of at least 10,000h</u>				
Carried to Summary				R
Section No. 4 ELECTRICAL ENGINEERING WORKS Bill No. 1 ELECTRICAL WORKS (PROVISIONAL) JMQS				

	<u>Recessed/surface mounted 1,2-meter two (2) lamp fluorescent luminaire complete with Prismatic diffuser, 2 x T8 LED tubular fluorescent, cool white lamp, electronic control gear and telescopic lamp holders as specified in the SANS 1119.</u>				
47	-Supply	No	12		
48	-Install	No	12		
	<u>Wall/Ceiling mounted round bulkhead luminaire complete with 20-Watt LED lamps. Similar or equal and approved to "Beka Series 30".</u>				
49	- Supply	No	24		
50	- Install	No	24		
	<u>Wall mounted rectangular bulkhead luminaire complete with eyelid, opal lens and 20-Watt LED lamp. Similar or equal and approved to "Beka Series 40".</u>				
51	- Supply	No	4		
52	- Install	No	4		
	<u>50mm x 180mm x 55mm 8W LED brick light, IP rating of 55 and above, similar or approved to "FUMAGALLI NINA190 BRICK LIGHT BLACK"</u>				
53	- Supply	No	32		
54	- Install	No	32		
	<u>Wall/Ceiling mounted round bulkhead luminaire complete with 20W. Similar or equal and approved to "Beka Series 300".</u>				
55	-Supply	No	21		
56	- Install	No	21		
Carried to Summary				R	
Section No. 4 ELECTRICAL ENGINEERING WORKS Bill No. 1 ELECTRICAL WORKS (PROVISIONAL) JM QS					

	<u>Wall mounted rectangular bulkhead luminaire complete with 24W complete with opal acrylic diffuser. Similar or equal and approved to "Regent Geo".</u>				
57	-Supply	No	4		
58	-Install	No	4		
	<u>Wall mounted LM 6 die cast aluminum and extruded aluminum, 2 x 17W LED. Similar or equal and approved to "Regent CUBICA DOUBLE"</u>				
59	- Supply	No	8		
60	- Install	No	8		
	<u>Surface mounted round downlight complete with 12W LED. Similar pr approved to "Regent Luxon Round Pro Backlight 160"</u>				
61	-Supply	No	38		
62	-Install	No	38		
	<u>45W 1200mm Ø LED Suspended light with Polycarbonate diffuser, aluminum housing and Powder coated finish. Similar or approved to "Regent Sky"</u>				
63	-Supply	No	4		
64	-Install	No	4		
	<u>Single Design Pendant Light LED Globe Circle Metal Electroplated Island Lights Bulb Base: E27, E26</u>				
65	-Supply	No	12		
66	-Install	No	12		
Carried to Summary				R	
Section No. 4					
ELECTRICAL ENGINEERING WORKS					
Bill No. 1					
ELECTRICAL WORKS (PROVISIONAL)					
JM QS					

<u>Black Or White Fitting: H132mm x W56mm x D127mm Reading Wall Light with ON/OFF Switch on the base complete with 1 x GU10, Max 10 Watt. similar or approved to "GU10 Spazio"</u>							
67	-Supply	No	7				
68	-Install	No	7				
<u>Wall mounted rectangular bulkhead luminaire complete with eyelid, opal lens and 20 Watt LED lamp. Similar or equal and approved to "Beka Series 40"</u>							
69	- Supply	No	17				
70	- Install	No	17				
<u>20W LED Floodlight, IP65</u>							
71	- Supply	No	2				
72	- Install	No	2				
<u>Fire resistant braai area light 7W-10W LED light fitting, Marine grade high-pressure die-cast aluminium, IP 66. Suitable for fire exposure. Similar or approved to "Beka LEDNOVA-MINI"</u>							
73	- Supply	No	4				
74	- Install	No	4				
<u>Surface/Recessed mounted Rectangular 1200mm x 300mm LED panel luminaire, similar or equal and approved to "Regent Luxon Rectangular 1200 x 600/ 50 Watt LED Panel".</u>							
75	- Supply	No	9				
76	- Install	No	9				
Carried to Summary							
Section No. 4							
ELECTRICAL ENGINEERING WORKS							
Bill No. 1							
ELECTRICAL WORKS (PROVISIONAL)							
JMQS							

	<u>LED, 201 Stainless Steel Bathroom Mirror Light or Picture Light with PC Diffuser, IP20, Color: Black – 9W LED (Included) Color Temp: 4000K Lumen: 540. Similar or approved to “Brightstar WB272 BLACK”</u>			
77	- Supply	No	8	
78	- Install	No	8	
	<u>7.2m Linear LED strip light fitting flush or recessed in the concrete as indicated in the drawing. Similar or approved to “Regent micro linear 33”</u>			
79	- Supply	No	3	
80	- Install	No	3	
	<u>LIGHT SWITCHES</u>			
	<u>Crabtree Classic light switch 100x50mm complete with coverplate and 100x50mm galvanised wall box (flush mount)</u>			
81	1-lever - 1 way - Supply	No	46	
82	- Install	No	46	
	<u>Crabtree Classic light switch 100x50mm complete with coverplate and 100x50mm galvanised wall box (flush mount)</u>			
	<u>1-lever, 2-way</u>			
83	-Supply	No	12	
84	-Install	No	12	
	<u>Crabtree Classic light switch 100x50mm complete with coverplate and 100x50mm galvanised wall box (flush mount)</u>			
	<u>2-lever, 1-way</u>			
85	-Supply	No	17	
	Carried to Summary			
	Section No. 4			
	ELECTRICAL ENGINEERING WORKS			
	Bill No. 1			
	ELECTRICAL WORKS (PROVISIONAL)			
	JMQS			

86	-Install	No	17		
	<u>Crabtree Classic light switch 100x50mm complete with coverplate and 100x50mm galvanised wall box (flush mount)</u>				
	<u>2-lever, 2-way</u>				
87	-Supply	No	8		
88	-Install	No	8		
	<u>Photoelectric Day/Night Sensors with Enclosure</u>				
89	-Supply	No	3		
90	-Install	No	3		
	<u>SMALL POWER & POWER SKIRTING</u>				
	<u>Provide Crabtree Classic socket outlet and isolators, 100x100mm complete with coverplate and 100x100mm galvanised wall box (flush mount). All socket outlets are required to have one three pin conventional plug and one RSA Euro/Diamond plug</u>				
	<u>Cover plates for socket outlets shall be of rust free metal, at least 1,2 mm thick. Paint finish shall be oven-baked enamel. The colour is as specified by the Architect or as reflected on the drawing</u>				
	<u>Single socket outlet 100mm x 100mm with diamond socket & new RSA Euro plug Flush mounted</u>				
91	- Supply	No	32		
92	- Install	No	32		
	<u>Double socket outlet 100mm x 100mm flush mounted</u>				
93	- Supply	No	44		
94	- Install	No	44		
	Carried to Summary				
	Section No. 4				
	ELECTRICAL ENGINEERING WORKS				
	Bill No. 1				
	ELECTRICAL WORKS (PROVISIONAL)				
	JM QS				

<u>Single socket outlet 100mm x 100mm with diamond socket, new RSA Euro and 2 USB charging points plug Flush mounted</u>					
95	- Supply	No	34		
96	- Install	No	34		
<u>Single socket outlet 100mm x 100mm with diamond socket & new RSA Euro plug Flush mounted in a water tight box</u>					
97	- Supply	No	5		
98	- Install	No	5		
<u>100x100x50mm wall boxes SABS approved galvanised pressed steel for building flush into brickwork or cast into concrete work - for socket outlets</u>					
99	- Supply	No	115		
100	- Install	No	115		
<u>100x50x50mm wall boxes SABS approved galvanised pressed steel for building flush into brickwork or cast into concrete work - for light switches</u>					
101	- Supply	No	79		
102	- Install	No	79		
<u>Unswitched 5A Socket outlets (for lights)</u>					
103	- Supply	No	181		
104	- Install	No	181		
<u>30A 2 Pole Isolator- for aircon and extraction fans</u>					
105	- Supply	No	20		
106	- Install	No	20		
Carried to Summary				R	
Section No. 4					
ELECTRICAL ENGINEERING WORKS					
Bill No. 1					
ELECTRICAL WORKS (PROVISIONAL)					
JMQS					

<u>10A 2 Pole Isolator - 100mm x 50mm Isolator flush mount (Guard house)</u>						
107	- Supply	No	2			
108	- Install	No	2			
<u>50A 2 Pole Isolator - for stove flush mounted</u>						
109	- Supply	No	4			
110	- Install	No	4			
<u>DATA & SATELITE TV OUTLET</u>						
<u>Supply and Install Data outlet on wall box at 400mm AFFL or as indicated on drawings</u>						
111	- Supply	m	23			
112	- Install	m	23			
<u>Supply and Install Satilite TV outlet on wall box at 1200mm AFFL or as indicated on drawings</u>						
113	- Supply	No	16			
114	- Install	No	16			
<u>POWER SKIRTING</u>						
<u>Supply and Install N8/P801 Steel 2 Compartment Power Skirting, Easter Oak, with End Caps, Slices and Accessories</u>						
115	- Supply	m	15			
116	- Install	m	15			
<u>Supply and Install Power Skirting Socket Outlet and Covers, Normal white</u>						
117	- Supply	No	3			
118	- Install	No	3			
Carried to Summary					R	
Section No. 4						
ELECTRICAL ENGINEERING WORKS						
Bill No. 1						
ELECTRICAL WORKS (PROVISIONAL)						
JMQS						

<u>Supply and Install Power Skirting Socket Outlet and Covers, Euro on power skirting</u>					
119	- Supply	No	3		
120	- Install	No	3		
<u>Supply and Install Power Skirting Socket Outlet and Covers, Dedicated Red</u>					
121	- Supply	No	3		
122	- Install	No	3		
<u>Supply and Install Power Skirting RJ45 Data Outlet with Cover</u>					
123	- Supply	No	3		
124	- Install	No	3		
<u>DISTRIBUTION BOARDS</u>					
<u>Supply and install Distribution Boards in accordance with SANS10142</u>					
<u>Distribution boards to comply to the requirements in the specification documents and on the schematics</u>					
<u>Shop drawings are required to be approved prior to manufacture</u>					
<u>DB.001 According to the specification and Schematics</u>					
125	- Supply	No	1		
126	- Install	No	1		
<u>DB.002 According to the specification and Schematics</u>					
127	- Supply	No	1		
128	- Install	No	1		
Carried to Summary				R	
Section No. 4					
ELECTRICAL ENGINEERING WORKS					
Bill No. 1					
ELECTRICAL WORKS (PROVISIONAL)					
JMQS					

<u>DB.003 According to the specification and Schematics</u>					
129	-Supply	No	1		
130	- Install	No	1		
<u>DB.004 According to the specification and Schematics</u>					
131	Supply	No	1		
132	Install	No	1		
<u>DB.G According to the specification and Schematics</u>					
133	- Supply	No	1		
134	- Install	No	1		
135	3-Phase meter installed inside the Kiosk	No	1		
<u>LIGHTNING PROTECTION AND EARTHING</u>					
<u>Supply and install lightning protection system in accordance with SANS10142-1. Copper Earthing straps to be bonded and earthed according to SANS10142.</u>					
<u>Provide an installation in accordance with the requirements of SANS62305-3.</u>					
<u>8m x 50mm² solid round aluminuim down conductor bonded to the roof sheeting, gutters, etc. and terminating in a flush mount test point enclosure</u>					
136	- Supply	No	10		
137	- Install	No	10		
<u>Test point enclosure with bi metallic connector, flush mounted to outside of structure</u>					
138	- Supply	No	10		
139	- Install	No	10		
Carried to Summary				R	
Section No. 4					
ELECTRICAL ENGINEERING WORKS					
Bill No. 1					
ELECTRICAL WORKS (PROVISIONAL)					
JM QS					

<u>3m x 50mm² stranded insulated copper conductor from lightning protection test point to earth spike, using appropriate connectors</u>			
140	- Supply	No	10
141	- Install	No	10
<u>1.5m copper clad steel SABS approved earth rods with clamp driven 1.35m away from the building</u>			
142	- Supply	No	10
143	- Install	No	10
144	All additional components required to bond and to complete the lightning protection installation to achieve the required resistance values		Item
145	Lightning Resistivity Testing post installation of earth electrodes and certification of lightning protection system by external specialist		Item
146	Type B earth electrode - 50mm ² stranded bare copper conductor trenched and installed 0.5m below ground level, connected to each earth spike with an appropriate connectors		Item
147	Add for profit		%
148	Add for general attendance		%
149	Bonding using 4mm ² copper straps to all equipment such as water heaters etc. as per SANS10142-1	m	1
<u>POWER SUPPLY</u>			
150	Application and payment of necessary fees to the Electrical supply authority including transformer, metering kiosk and necessary cabling infrastructure required for a 32kVA supply		Item
151	Add for profit		%
152	Add for general attendance		%
Carried to Summary			R
Section No. 4 ELECTRICAL ENGINEERING WORKS Bill No. 1 ELECTRICAL WORKS (PROVISIONAL) JMQS			

SOLAR SOLUTION

The solar system must be installed by a qualified electrician in possession of a solar Green card. The final installation must be certified by a professional engineer.

SOLAR PANELS

8kW Hybrid solar inverter. NRS approved. SUNSYNK, SOLIS or other approved brand with all necessary interface modules and connections for masters & slaves , electrical cables and data communication unit,router with Ethernet connection, connectable in parallel and modularly extendable. The Inverter must include the following concepts such as (Ac and DC coupling, High efficiency, intelligent battery management for maximum battery life, charge level calculation, extreme overload capability, and battery temperature sensing and battery current measurements) - For each Unit

153	- Supply	No	4	
-----	----------	----	---	--

154	- Install	No	4	
-----	-----------	----	---	--

3,6kW Hybrid solar inverter. NRS approved. SUNSYNK, SOLIS or other approved brand with all necessary interface modules and connections for masters & slaves , electrical cables and data communication unit,router with Ethernet connection, connectable in parallel and modularly extendable. The Inverter must include the following concepts such as (Ac and DC coupling, High efficiency, intelligent battery management for maximum battery life, charge level calculation, extreme overload capability, and battery temperature sensing and battery current measurements) - For Guard House

155	- Supply	No	1	
-----	----------	----	---	--

156	- Install	No	1	
-----	-----------	----	---	--

Carried to Summary

R

Section No. 4
ELECTRICAL ENGINEERING WORKS
Bill No. 1
ELECTRICAL WORKS (PROVISIONAL)
JMQS

[illegible]

	<u>10kW Lithium Ion "Freedom Won" Batteries or similar or approved brand are acceptable at the engineers discretion. The batteries must provide high-quality and achieving superior performance, the manufacturing date must be new and suitable for every type of applications especially for solar renewable energy, designed Service Life 10 years with low internal resistance, designed to be deeply discharged. The Battery should provide benefits of being maintenance free, case flame retardant & non-hazardous. The price Includes supply, install & connect Battery temp. sensor (BTS).The contractor must submit manufacturer warranty for batteries for a period 10 years. - For each Unit</u>				
165	- Supply	No	8		
166	- Install	No	8		
	<u>5kW Lithium Ion "Freedom Won" Batteries or similar or approved brand are acceptable at the engineers discretion. The batteries must provide high-quality and achieving superior performance, the manufacturing date must be new and suitable for every type of applications especially for solar renewable energy, designed Service Life 10 years with low internal resistance, designed to be deeply discharged. The Battery should provide benefits of being maintenance free, case flame retardant & non-hazardous. The price Includes supply, install & connect Battery temp. sensor (BTS).The contractor must submit manufacturer warranty for batteries for a period 10 years. - For Guard house</u>				
167	- Supply	No	1		
168	- Install	No	1		
	<u>DC Inline Fuse & MC4 connectors per string (positive & negative)</u>				
169	- Supply	No	18		
170	- Install	No	18		
Carried to Summary				R	
Section No. 4 ELECTRICAL ENGINEERING WORKS Bill No. 1 ELECTRICAL WORKS (PROVISIONAL) JM QS					

[illegible]

<u>Earthing System for Battery Bank</u> <u>Supply,install,connect and operate complete independent earthing system for Battery Banks system, must be separated of the main earthing system to obtain 2 ohm max resistance. the item includes (2 copper electrodes 15mm² driven into ground, manholes with iron cover, earth joints, clamps, ducts , conduits and 50 mm² flexible earthing copper wires and cables from the Negative bus bar in the battery fuse box to the electrode to complete the system as specifications and engineer instruction's and approval. The earthing should be done for each battery bank installed in each house unit</u>							
179	- Supply	No	5				
180	- Install	No	5				
<u>Earthing System for PV System</u> <u>Supply,install,connect and operate complete independent earthing system for PV solar system, must be separated of the main earthing system to obtain 2 ohm max resistance. the item includes (2 copper electrodes 15mm² driven into ground, manholes with iron cover, earth joints, clamps, ducts , conduits and 25 mm² flexible earthing copper wires and cables from the PV system components to the electrode to complete the system as specifications and engineer instruction's and approval.</u>							
181	- Supply	No	10				
182	- Install	No	10				
<u>Supply and Install P2000 Trunking complete with accessories</u>							
183	- Supply	m	100				
184	- Install	m	100				
185	Supply and Install ECO RUBBER waterproofing for PV system and associated equipment		Item				
Carried to Summary						R	
Section No. 4 ELECTRICAL ENGINEERING WORKS Bill No. 1 ELECTRICAL WORKS (PROVISIONAL) JMQS							

<u>Supply and Install Onesto DIN slim indication lights in each house unit DB board</u>			
186	- Supply	No	8
187	- Install	No	8
<u>Supply and Install signage indicating dual electrical supply for DB in each house unit</u>			
188	- Supply	No	4
189	- Install	No	4
<u>200A double pole isolator (fused) for battery disconnection</u>			
190	- Supply	No	4
191	- Install	No	4
<u>100A double pole isolator (fused) for battery disconnection</u>			
192	- Supply	No	1
193	- Install	No	4
194	Certification of Solar Solution for each house unit and guard house	No	5
<u>ELECTRIC FENCE</u>			
195	Provision of a supply and installation of Electrical fence around the boundary wall, including energiser, cabling, earthing, signage, protecting devices and certification	Item	150 000.00
196	Add for profit	%	
197	Add for general attendance	%	
<u>CCTV SYSTEM</u>			
Carried to Summary			R
Section No. 4			
ELECTRICAL ENGINEERING WORKS			
Bill No. 1			
ELECTRICAL WORKS (PROVISIONAL)			
JMQS			

	<u>12 Channel NVR</u>						
198	- Supply	No	1				
199	- Install	No	1				
	<u>Infra Red 4MB avigilon bullet camera</u>						
200	- Supply	No	9				
201	- Install	No	9				
	<u>1TB Hard drive</u>						
202	- Supply	No	1				
203	- Install	No	1				
	<u>42'' Plasma Screen</u>						
204	- Supply	No	1				
205	- Install	No	1				
	<u>Cat 6 cable</u>						
206	- Supply	m	200				
207	- Install	m	200				
208	Installing and Commissioning		Item				
209	Provide manuals and technical literature for the system and its components		Item				
210	Any additional items required for the successful completion of the above			SUM			
	<u>ALARM SYSTEM</u>						
211	Provision of a supply and installation of alarm system.		Item			90 909.09	
212	Add for profit			%			
	Carried to Summary			R			
	Section No. 4						
	ELECTRICAL ENGINEERING WORKS						
	Bill No. 1						
	ELECTRICAL WORKS (PROVISIONAL)						
	JMQS						

213 Add for general attendance

%

Carried to Summary

R

Section No. 4
ELECTRICAL ENGINEERING WORKS
Bill No. 1
ELECTRICAL WORKS (PROVISIONAL)
JMQS

<p>Section No. 4</p> <p>Bill No. 1</p> <p>ELECTRICAL WORKS (PROVISIONAL)</p> <p><u>SUMMARY</u></p>			
<p>Total Brought Forward from Page No.</p>	<p>Page No</p> <p>110</p> <p>111</p> <p>112</p> <p>113</p> <p>114</p> <p>115</p> <p>116</p> <p>117</p> <p>118</p> <p>119</p> <p>120</p> <p>121</p> <p>122</p> <p>123</p> <p>124</p> <p>125</p> <p>126</p> <p>127</p> <p>128</p>		<p>Amount</p>
<p>Section No. 4</p> <p>ELECTRICAL ENGINEERING WORKS</p> <p>Bill No. 1</p> <p>ELECTRICAL WORKS (PROVISIONAL)</p> <p>JMQS</p>	<p>Carried Forward</p>	<p>R</p>	

Section No. 4			
Bill No. 1			
ELECTRICAL WORKS (PROVISIONAL)			
<u>SUMMARY</u>			
	Page No		Amount
Brought Forward		R	
Total Brought Forward from Page No.	129		
	130		
	131		
	132		
	133		
	134		
	135		
Total Carried to Final Summary		R	
Section No. 4			
ELECTRICAL ENGINEERING WORKS			
Bill No. 1			
ELECTRICAL WORKS (PROVISIONAL)			
JMQS			

6 Wall Mounted Extractor Fan
Supply, delivery, installation of 27l/s Wall Mounted
Extractor Fan complete with sleeve, and electrical wiring

No

4

Carried to Summary

R

Section No. 5
MECHANICAL ENGINEERING WORKS
Bill No. 1
HVAC
JMQS

Section No. 5

Bill No. 1

HVAC

SUMMARY

Total Brought Forward from Page No.

**Page
No**

138

139

Amount

Carried Forward to Summary of Section No. 5

Section No. 5

MECHANICAL ENGINEERING WORKS

Bill No. 1

HVAC

JMQS

R

5	22mm 90 deg elbow	No	34
6	22mm x 22 mm x 22 mm Tee	No	32
7	22mm x 22 mm x 15 mm Tee	No	68
8	15mm polypropylene pipe for reticulation network	m	45
9	15mm 90 deg elbow	No	12
10	15mm x 15mm x 15mm Tee	No	
11	35mm - 22mm Reducer	No	8
12	22mm - 15mm Reducer	No	16
13	35mm Lockable Isolating Valves	No	8
14	22mm Lockable Isolating Valves	No	34
15	15mm Lockable Isolating Valves	No	48
<u>Hot Water reticulation including insulation and cladding</u>			
16	Pipe Brackets, Supports and Hanger (for both supply and return hot water)		Item
17	Pipework insulation for a 22mm diameter pipe (25mm thick glass fibre or mineral wool), complete with cladding as specified	m	172
18	Pipework insulation for a 15mm diameter pipe (25mm thick glass fibre or mineral wool), complete with cladding as specified	m	25
<u>Domestic Water Booster Pump</u>			
19	Domestic Water Pump (50l/s @ 300kPa), complete with non-return valve	No	4
20	Testing Precommissioning Tests, Pressure Tests, including all statutory tests		Item
Carried to Summary			
Section No. 5 MECHANICAL ENGINEERING WORKS Bill No. 2 WET SERVICES JMQS			

Section No. 5

Bill No. 2

WET SERVICES

SUMMARY

Total Brought Forward from Page No.

**Page
No**

141

142

Amount

Carried Forward to Summary of Section No. 5

Section No. 5

MECHANICAL ENGINEERING WORKS

Bill No. 2

WET SERVICES

JMQS

R

R

16	110mm Lockable Isolating Valves	No	12
17	75mm Lockable Isolating Valves	No	4
18	50mm Lockable isolating Valves	No	12
19	Supply, delivery, installation and commissioning of gully trap complete excluding building work (Gully Base by Main contractor)	No	8
20	Supply, delivery, installation and commissioning of 110mm Vent Valve	m	12
21	Supply, delivery, installation and commissioning of 50mm P-trap on airconditioning drainage pipes	m	4

DRAINAGE (PROVISIONAL)

PREAMBLES

For preambles see "Specification of materials and methods to be used - PW 371"

Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to.

Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.

SUPPLEMENTARY PREAMBLES

Tenderers to issue workshop drawings and builders work drawings

Tenderers to make allowance for:

- drawings in electronic format
- Operation and maintenance manuals
- One year written guarantee and maintenance for 12 months.
- Training of client's staff
- Painting and marking

Carried to Summary

Section No. 5
MECHANICAL ENGINEERING WORKS
Bill No. 3
DRAINAGE
JMQS

R

<p>Section No. 5</p> <p>Bill No. 3</p> <p>DRAINAGE</p> <p><u>SUMMARY</u></p>				
Total Brought Forward from Page No.	Page No		Amount	
	144			
	145			
Carried Forward to Summary of Section No. 5			R	
<p>Section No. 5</p> <p>MECHANICAL ENGINEERING WORKS</p> <p>Bill No. 3</p> <p>DRAINAGE</p> <p>JMQS</p>				

[illegible]

[illegible]

[illegible]

[illegible]

Bill No	SUMMARY - MECHANICAL ENGINEERING WORKS	Page No	Amount R c
1	HVAC	140	
2	WET SERVICES	143	
3	DRAINAGE	146	
4	FIRE WATER AND EQUIPMENT	149	
5	LP GAS RETICULATION AND EQUIPMENT	152	
Total Carried to Final Summary			R
Section No. 5 MECHANICAL ENGINEERING WORKS JMQS			

Item No	Quantity	Rate	Amount
<u>BILL NO. 1</u>			
<u>PROVISIONAL SUMS</u>			
<u>PREAMBLES</u>			
For preambles see " Specification of materials and methods to be used - PW 371"			
Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to.			
Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.			
<u>SUPPLEMENTARY PREAMBLES</u>			
<u>Cash discount</u>			
No cash discount. All provisional sums are "NET"			
<u>Fuel, power and water for commissioning plant</u>			
The cost of water, power and fuel for the commissioning of plant shall be borne by the Selected or Nominated Sub-contractor appointed for the relevant selected or nominated sub-contract works in terms of the conditions under which they have/are contracted for the specialist work involved			
<u>Community Liaison Officer (CLO)</u>			
The CLO's duties will include EPWP reporting on a monthly basis			
The Contractor must issue copies of CLO's payslips tpo the PA and IDT on a monthly basis			
Carried to Summary			
Section No. 6 PROVISIONAL SUM Bill No. 1 PROVISIONAL SUMS JMQS			R

BILL NO. 1

PROVISIONAL SUMS

PREAMBLES

For preambles see " Specification of materials and methods to be used - PW 371"

Relevant parts of the SANS10400 Series of Standards and application of the National Building Regulations form part of the specification and shall be strictly adhered to.

Relevant parts of the SANS2001 Series of Standards form part of the specification and shall be strictly adhered to.

SUPPLEMENTARY PREAMBLES

Cash discount

No cash discount. All provisional sums are "NET"

Fuel, power and water for commissioning plant

The cost of water, power and fuel for the commissioning of plant shall be borne by the Selected or Nominated Sub-contractor appointed for the relevant selected or nominated sub-contract works in terms of the conditions under which they have/are contracted for the specialist work involved

Community Liaison Officer (CLO)

The CLO's duties will include EPWP reporting on a monthly basis

The Contractor must issue copies of CLO's payslips to the PA and IDT on a monthly basis

Carried to Summary

R

Section No. 6
PROVISIONAL SUM
Bill No. 1
PROVISIONAL SUMS
JMQS

PROVISIONAL SUM

Bill No. 1

PROVISIONAL SUMS

JMQS

Profit

Provisional sums are net and do not include builder's discount. The Contractor may allow next to "Profit" items for any profit he might consider necessary

Attendance

It will be expected from the Contractor to render all general attendance and, if specifically so described, special attendance services to each relevant Specialist, all in accordance with the Clauses set out in the "Preliminaries" section

The item "Attendance" which follows each of the provisional sums for nominated and/or selected sub-contractors' work, shall be deemed to cover all the contractor's costs incurred in providing free of charge to the Nominated and/or Selected Sub-contractors, the following:

- 1 The services as set out in the clauses in the "Preliminaries" section
- 2 Making good in all trades and cleaning down and removal of rubbish on completion

The Contractor may allow next to "Attendance" items for the recovery of such costs he might consider necessary

Also refer to the Clauses in the "Preliminaries" section for the definitions and adjustment of "Attendance" and "Special Attendance" respectively

All provisional sums cover the supply and installation of material, equipment, plant, etc., including the commissioning thereof, where applicable

Community Liaison Officer

- 1 Provide the amount of R150,000.00 (One hundred and fifty thousand rand) for community liaison officer
- 2 Allow for profit on above if required
- 3 Allow for attendance

Item

150 000.00

%

%

Carried to Summary

R

Section No. 6
PROVISIONAL SUM
Bill No. 1
PROVISIONAL SUMS
JM QS

<u>Loose Furniture & Appliances</u>				
4	Provide the amount of R1 800,000.00 (One million eight hundred thousand rand) for loose furniture and appliances	Item		1 800 000.00
5	Allow for profit on above if required		%	
6	Allow for attendance		%	
<u>Appliances</u>				
7	Provide the amount of R370,000.00 (Three hundred and seventy thousand rand) for appliances	Item		370 000.00
8	Allow for profit on above if required		%	
9	Allow for attendance		%	
<u>Curtains & Blinds</u>				
10	Provide the amount of R230,000.00 (Two hundred and thirty thousand rand) for blinds and curtains	Item		230 000.00
11	Allow for profit on above if required		%	
12	Allow for attendance		%	
<u>Built-In Cupboards and Worktops</u>				
13	Provide the amount of R1 200,000.00 (One million two hundred thousand rand) for joinery and fittings	Item		1 200 000.00
14	Allow for profit on above if required		%	
15	Allow for attendance		%	
<u>Sanitary plumbing</u>				
16	Provide the amount of R30,000.00 (Thirty thousand rand) for sanitary plumbing	Item		30 000.00
17	Allow for profit on above if required		%	
Carried to Summary			R	
Section No. 6 PROVISIONAL SUM Bill No. 1 PROVISIONAL SUMS JMQS				

UNIVERSITY OF VENDA
CONSTRUCTION OF NEW SMC RESIDENCES
THOHOYANDOU BLOCK D

18	Allow for attendance		%	
	<u>Sanitary fittings</u>			
19	Provide the amount of R50,000.00 (Fifty thousand rand) for sanitary fittings	Item		50 000.00
20	Allow for profit on above if required		%	
21	Allow for attendance		%	
	<u>Sewer, water and fire reticulation works</u>			
22	Provide the amount of R200,000.00 (Two hundred thousand rand) for sewer reticulation works	Item		200 000.00
23	Allow for profit on above if required		%	
24	Allow for attendance		%	
	<u>Root barriers</u>			
25	Provide the amount of R50,000.00 (Fifty thousand rand) for root barriers	Item		50 000.00
26	Allow for profit on above if required		%	
27	Allow for attendance		%	
	<u>Drainage layer</u>			
28	Provide the amount of R50,000.00 (Fifty thousand rand) for drainage layer	Item		50 000.00
29	Allow for profit on above if required		%	
30	Allow for attendance		%	
	<u>Landscaping</u>			
31	Provide the amount of R70,000.00 (Seventy thousand rand) for landscaping layer	Item		70 000.00
32	Allow for profit on above if required		%	
Carried to Summary			R	
Section No. 6 PROVISIONAL SUM Bill No. 1 PROVISIONAL SUMS JMQS				

[illegible]

Section No. 6

Bill No. 1

PROVISIONAL SUMS

SUMMARY

Total Brought Forward from Page No.

**Page
No**

Amount

154

155

156

157

158

Total Carried to Final Summary

R

Section No. 6

PROVISIONAL SUM

Bill No. 1

PROVISIONAL SUMS

JMQS

Section No		Page No	Amount R c	
FINAL SUMMARY				
1	PRELIMINARIES	18		
2	BUILDING WORKS	86		
3	EXTERNAL WORKS	109		
4	ELECTRICAL ENGINEERING WORKS	137		
5	MECHANICAL ENGINEERING WORKS	153		
6	PROVISIONAL SUM	159		
Sub-Total			R	
ADD: Value-Added Tax @ 15%			R	
Sub-Total			R	
Total Carried to Tender Form			R	
JMQS				